



Final Report

Literature Search

Chattahoochee-Flint
Regional Development Center

Franklin, Georgia

April 1, 1998

CHATTAHOOCHEE - FLINT STUDY

Table of Contents

EXECUTIVE SUMMARY	2
LITERATURE SEARCH: CHATTAHOOCHEE - FLINT STUDY	4
MODELING	4
MODELING PRINCIPLES	9
GEOGRAPHICAL INFORMATION SYSTEMS AND MODELING	10
URBAN DEVELOPMENT AND SEDIMENT CONTROL	11
PARTICLE SIZE AND SETTLING	12
TURBIDITY	14
COST EFFECTIVENESS	17
SCREENING FOR NEEDED MODEL CAPABILITIES	18
LEVEL I SCREENING - GENERAL STORMWATER, SEDIMENT, AND SEDIMENT SIZE	18
LEVEL II SCREENING - GENERAL SEDIMENT COMPUTATION REQUIREMENTS	19
LEVEL III SCREENING - SPECIFIC PREDICTION TECHNOLOGY REQUIREMENTS	20
SALIENT POINTS ABOUT PREDICTION CAPABILITIES NOT CURRENTLY AVAILABLE IN ANY MODEL	22
Turbidity	22
Economics	23
RECOMMENDATIONS	23
REFERENCES CITED	25
APPENDIX - ADDITIONAL REFERENCES	30
GOVERNMENT REFERENCES	30
OTHER RELEVANT REFERENCES	32

EXECUTIVE SUMMARY

The Chattahoochee-Flint Regional Development Center (CFRDC) requested a literature search to document the development of a state-of-the-practice approach to the design of cost-effective, comprehensive erosion prevention and sediment control systems that may be reasonably expected to meet a water quality performance specification. The literature evaluation was to consider computer modeling widely available to design professionals and regulators. In addition, efforts were made to locate newly available materials that could direct and shape further computer modeling and public information phases of the project. Specific goals of this effort were to search all reasonably available data sources using applicable topic areas and to locate relevant data sources and performance information that closely relate to the Chattahoochee Basin.

The Woolpert team used a multifaceted approach to accomplish the goals and objectives identified for the literature review. Electronic databases, university libraries, and personal libraries were used to locate available information in a timely manner. To take advantage of these databases, the Woolpert team, in conjunction with CFRDC personnel, developed a list of key words and combinations of key words. These keywords were used in keyword and subject searches to generate “hits” in electronic data bases. In addition, the Woolpert team used internal and external sources of its personnel to locate unpublished information through networking, Internet, professional memberships, and current research.

As information was found, it was screened for relevancy to project needs and potential application to the Chattahoochee Basin. A meeting between Woolpert team members (Spearman, Holbrook, Hayes, and Barfield) with representatives of CFRDC was held on February 27, 1998 to refine the goals and objectives. At this meeting, the CFRDC representatives clearly emphasized that they were particularly interested in identifying the capabilities of available models and innovative practices that might be applicable to control erosion and sediment from construction in the Chattahoochee Basin. They requested this information with a rapid turnaround because of its timeliness relative to other ongoing efforts. Commonly used structures and methods were of little interest unless they made a connection between sediment concentration and turbidity or dealt with topics like efficiency and cost effectiveness. Thus, the Woolpert team placed considerable emphasis on searching the literature for potentially appropriate models and their capabilities. A draft report on model findings was submitted March 17, 1998. The most significant aspect of this report was the three tier screening processes which delineated the features of numerous models. This screening led to tables that are also included in this report.

In order to accomplish the other objectives of the literature search, the Academic ASAP database and the Monthly Catalog of Government Publications database were initially searched using keywords and subjects that were previously submitted to the Committee.

This initial search of Academic ASAP developed a reference listing containing approximately 6000 articles as found in Volume I. These are based on keywords and keyword combinations as shown in Volume I. The keywords were also used in a subject search of Academic ASAP with results shown in Volume II. Similarly, the search of the Monthly Catalog of Government Publications database led to the listing shown in Volume III. This large listing of articles was filtered by reading through each title and publication listing to determine the most relevant articles. This led to the references that are shown in the Appendix. The Appendix lists some 300 literature references that were considered to be somewhat relevant to the effort but were not necessarily deemed to be as closely aligned to the project as the cited references. They are arranged in the Appendix by year since this is the manner in which the search took place and because many of the references involve several keywords. Abstracts for these 300 articles were evaluated and further filtered for relevance to the Chattahoochee-Flint Project and more extensive review. This summary of the most relevant articles is contained in the following sections of this report. The digital version of this section can easily be searched for keywords or phrases using a browser or word processor.

Volume IV contains approximately 300 abstracts for these potentially useful articles. No attempt was made to group them by topic since most articles would fit under several topics. They are available in digital form and can easily be searched for keywords or phrases using a browser or word processor. Full documentation of the source is also provided so that these publications can be easily located. Copyright limitations prevent the inclusion of complete manuscripts for all articles.

LITERATURE SEARCH: CHATTAHOOCHEE - FLINT STUDY

Countless articles have been written describing the impacts and sources of erosion and sediment. Historically, emphasis on erosion control began in the agricultural areas because the loss of topsoil was seen as an economic loss. More recently, methods of estimating soil loss and sediment yield have been applied to other activities such as timber harvesting, mining, and urban construction. In many cases, this work has included developing relationships for a wider range in conditions or as a result of specific actions that are necessary to conduct the activity. Limited emphasis has been placed on relating the cost of on-site erosion prevention and sediment control to off-site water quality. The following information summarizes recent literature that appears to relate in-stream turbidity with on-site erosion prevention and sediment control. Another consideration is providing cost-effective prevention and controls. This is also addressed.

In order to accomplish the objectives of the literature search, the Academic ASAP database and the Monthly Catalog of Government Publications database were initially searched using keywords and subjects that were previously submitted to the Committee. A listing of these keywords is shown in Table 1. This initial search developed a reference listing for approximately 6000 articles. This large listing was filtered by going through the title and publication for the most relevant articles. This led to the references that are shown in the Appendix. The Appendix contains some 300 literature references that were considered to be somewhat relevant to the effort but were not necessarily deemed to be closely aligned to the project as the cited references. Abstracts for these 300 articles were evaluated and further filtered for relevance to the Chattahoochee-Flint Project and more extensive review. The following sections summarize the most relevant of these articles. For further information concerning the process, references, abstracts, or availability of full publications, please contact Woolpert.

A subsequent section deals specifically with the screening of available models relative to their features that relate to this study. The results shown in the model matrices are based on information gleaned from numerous published or unpublished articles and experience of the Woolpert Team.

MODELING

A particularly useful publication was published by the Department of Environmental Conservation and the Soil and Water Conservation Committee as NYS (1994). This publication compares a variety of models with respect to their ability to predict pollutant loading. Unfortunately, many of the models presented do not include sediment movement as a component. The erosion and sediment related models are presented in

the later section dealing with model screening. Numerous mathematical models to predict capability for soil and water erosion under global change have been developed (Nearing et al., 1996). One of these models is the Erosion-Productivity Impact Calculator (EPIC) model which was originally developed to assess the effect of soil erosion on soil productivity. The model has been expanded and refined to allow simulation of many processes important in agricultural management. EPIC is a continuous simulation model that can be used to determine the effects of management on agricultural production and soil and water resources. Drainage areas considered by EPIC are generally field-sized, up to 100 ha with weather, soils, and management systems assumed to be homogeneous. The major components in EPIC are weather simulation, hydrology, erosion-sedimentation, nutrient cycling, pesticide fate, plant growth, soil temperature, tillage, economics, and plant environment control. Another model, Water Erosion Prediction Project (WEPP), is a new generation of soil erosion prediction technology for use in soil and water conservation planning and assessment. WEPP is physically-based on rill and interrill erosion processes and sediment transport mechanics. It does not use principles, parameters, or logic from the USLE for predicting erosion. Since it is mostly process-based, the model is well suited for studying effects of environmental system changes on hydrologic and erosion processes. WEPP is a continuous simulation model and works primarily on a daily time step in terms of updating system parameters that define the surface conditions. The WEPP model includes eight major components: climate, infiltration, water balance, plant growth and residue decomposition, tillage and consolidation, surface runoff, erosion, and winter processes. The erosion part uses a steady-state sediment continuity equation to calculate net values of detachment or deposition rates along the hillslope profile and in watershed channels. The erosion process is divided into channel, rill, and interrill portions where interrill areas serve to direct sediment to the rills, or small channel flows. Hillslopes direct sediment to watershed channels. Within rills and channels the sediment may be carried downslope or deposited. Scour by rill and channel flow is calculated when flow shear exceeds critical shear of the soil and when sediment load is less than calculated sediment capacity.

The Water Erosion Prediction Project (WEPP) model was developed to replace the Universal Soil Loss Equation (Lafren, 1997). Since the USLE has been used worldwide for years, its replacement as a tested technology required years of extensive research on soil erodibility. WEPP will serve as a tool in helping managers choose the best way to produce on and protect a specific farm based on its soil, topography and climate.

WEPP is a computer simulation model of soil erosion and sediment transport that was the result of a research program that was initiated by the agricultural Research Service and Natural Resource Conservation Service in 1985 (Lafren et al., 1997). The WEPP model provides daily predictions of soil erosion based on environmental parameters. The computer model can be utilized for the development of soil erosion practices, watershed rating or classification and forest management.

The ability to predict sediment yield from catchments for studies of reservoir sedimentation, morphologic modeling, and soil-conservation planning was considered by Kothyari et al. (1994). They recognized that although records on sediment yield are generally not available, sediment yield can be predicted from other commonly available hydrologic data in the literature. Their study compared some of these methods for their accuracy using carefully collected data from experimental catchments. They found that existing methods do not adequately account for the process of sediment delivery; these methods produce less accurate prediction of sediment yield. As a result, they proposed a new method based on the routing of surface erosion through time-area segments. This method was found to estimate sediment yield more accurately than those it was compared with. The proposed method has a more sound basis for further use in distributed models.

A relatively original point of view was introduced by Menendez (1997) in order to classify sedimentation phenomena according to spatial scale. Three categories are identified: large-, medium-, and short-scale models. The distinction is made between the hydrodynamic adaptation length and the study scale. This allows determination of the right mathematical model for each particular case. The main features of the models involved and of the associated numerical methods are briefly described.

Although most soil erosion studies are confined to short time frames and small plot scales, Kirkby et al. (1996) expanded soil erosion studies to increase the understanding of the relationship between global climatic change and soil erosion. Scientists have developed dynamic systems strategies to integrate spatial variations between small and large scale erosion studies into a new soil erosion monitoring and experimentation model.

A non-point source pollution management model, ANSWERS-2000, was developed by Bouraoui and Dillaha (1996) to simulate long-term average annual runoff and sediment yield from agricultural watersheds. The model is based on the event-based ANSWERS model and is intended for use without calibration. The Green-Ampt infiltration equation was incorporated into ANSWERS-2000 to improve estimates of infiltration. An evapotranspiration submodel was added to permit long-term, continuous simulation. The model was validated without calibration using data from field-sized watersheds in Watkinsville, Ga. Additional validation with limited calibration was done on the Owl Run watershed in Virginia. Model predictions of cumulative sediment yield were within 12% and 68% of observed values. Predicted cumulative runoff volumes ranged from 3% to 35% of observed values. Predictions of sediment yield and runoff volume for individual storms were less accurate, but generally within 200% of observed.

A basin-scale model was developed by Cooper and Bottcher (1993) to simulate long-term average losses of water, sediment, and nutrients from large rural watersheds. In addition to simulating diffuse sources using the Chemicals, Runoff, and Erosion from

Agricultural Management Systems (CREAMS) model, the model incorporates point sources, nitrogen leaching from septic tanks, riparian and stream channel attenuation processes, and routing algorithms. Predictions of long-term average sediment and nutrient losses were generally within 30% of those estimated from data gathered at the basin outlet.

A model was developed to simulate suspended transport of fine-grained sediment, both cohesive and noncohesive, in the Pawtuxet River, Rhode Island (Ziegler Bradley Nisbet, 1994). The model utilizes results of extensive laboratory and field studies to specify parameters governing deposition and resuspension processes. The SEDZL modeling framework, which accurately and realistically simulates cohesive resuspension and deposition, including the effects of flocculation, has been modified to include simulation of noncohesive suspended transport. Field studies were conducted during the spring of 1992 to collect bathymetric, stage-height, suspended-solids, and sediment-bed data. The hydrodynamic and sediment transport models were calibrated and validated during a 33-day period, which included two high-flow events, each of which approximately correspond to the annual flood. Successful calibration indicated that the model has potential as a predictive tool.

A method for determining data required to reduce model-prediction uncertainty using first-order reliability analysis was developed (Melching and Yoon, 1996). They demonstrated the uncertainties in simulation of stream water quality for the Passaic River, NJ, with the QUAL2E model. Results may suggest that water-quality modelers and planners do similar reliability analyses for more efficient sampling programs.

Arnolds et al., (1995) discussed the use of simulation models to evaluate the impact of changes in land use and agricultural management on streamflow and sediment yields from watersheds and river basins. Current agricultural-management models are limited by spatial scale, and river-basin models do not simulate land use and management adequately to evaluate management strategies. A model called ROTO (routing outputs to the outlet) was developed to estimate water and sediment yield on large basins (several thousand square miles). ROTO is a continuous model operating on a daily time step that accepts inputs from continuous-time, soil-water balance models. Components for water and sediment movement in channels and reservoirs are developed within a comprehensive basin-scale agricultural management model. The model was validated on three different spatial scales: the small watershed, watershed, and river basin.

An in-place pollutant export model (IPX) was used by Velleux et al. (1996) as a screening-level model for estimating contaminant export from tributaries with contaminated sediments to receiving water bodies. IPX is a modified version of the USEPA's WASP4 modeling framework. IPX synthesizes sediment transport processes for sediment aging, decreased sediment resuspendability, and resuspension of deposited sediments as a function of water velocity, into an expanded WASP4 contaminant

transport framework. These process descriptions are needed to accurately simulate contaminant transport and substantially improve the framework for application to tributary systems subject to significant deposition and resuspension events. The potential for applying IPX is broad; water quality impairments attributable to contaminated sediments are widespread due to discharges from industry, agriculture, and mining and ore processing.

CE-QUAL-ICM is a three-dimensional, time-variable, eutrophication model that uses 22 variables that include physical properties; multiple forms of algae, carbon, nitrogen, phosphorus, and silica; and dissolved oxygen (Cercio and Cole, 1993). Application in the Chesapeake Bay indicates the model successfully simulates water-column and sediment processes that affect water quality. Phenomena simulated include formation of the spring algal bloom subsequent to the annual peak in nutrient runoff, onset and breakup of summer anoxia, and coupling of organic particle deposition with sediment-water nutrient and oxygen fluxes.

A highly urbanized watershed near Boston was used by Solo-Gabriele and Perkins (1997) to evaluate whether streamflow can be separated into three separate components: quick storm flow, slow storm flow, and long-term baseflow. Quick storm flows were thought to activate highly sources of sediment from outside the river and result in large increases in concentrations during storm events. Slow storm flows and long-term base flows result in low and relatively constant suspended sediment concentrations. Net concentration of dissolved and particulate metals observed in the river is a result of mixing the components. Differences between subbasins can be addressed by stream flow.

Runoff and sediment yield for 30 runoff events on three experimental watersheds were calculated using the agricultural non-point-source pollution (AGNPS), areal non-point-source watershed environmental response simulation (ANSWERS), and chemicals runoff and erosion from agricultural management systems (CREAMS) runoff-erosion models by Wu et al. (1993). Results compared with measured runoff and sediment yield show reasonable to poor agreement for runoffs. The average ratios of computed to measured sediment yields for the various storms and watersheds show a large scatter. ANSWERS provides the most consistent results for estimates of runoff and sediment yield. All three models tend to underestimate sediment yield for large storms.

MODELING PRINCIPLES

Walker (1994) published a study on effectiveness of various management practices in small rural lakes and streams at the watershed scale. Statistical techniques were used to

test for changes in water-quality data from watersheds where best management practices (BMPs) were implemented. Reductions in data variability due to climate and seasonality were compared through the use of regression methods. He also discussed the merits of using storm-mass-transport data to improve the ability to detect BMP effects on stream-water quality. In all cases, the use of regressions improved the ability to detect trends.

Wu et al. (1996) monitored three urban wet detention ponds in the Piedmont of North Carolina to investigate long-term pollutant removal as a function of surface to area ratios. Eleven storm events were monitored over a sampling period of 13 months. Urban runoff originating from the study area was characterized by event-mean concentrations for total suspended solids (135 mg/L), total Kjeldahl nitrogen (0.88 mg/L), total iron (6.11 mg/L), and total zinc (66ug/L). Observed event-mean concentrations were generally lower than national values reported by the Nationwide Urban Runoff Program. Particle sizes of sediment discharged in runoff were found to be much finer than the national averages due to the predominant clayey soils in the region. This study demonstrated that surface to area ratio can be a useful predictor of wet pond performance. Utilizing 1-2% of watershed area for development of wet detention ponds at strategic locations could reduce pollutant loadings to meet targeted requirements of water quality improvement.

The varying velocities of flood waves and stream flow can be a major consideration relating stream discharge to suspended sediment concentrations according to Marcus (1989). Flood waves move downstream faster than the flow velocity, thus leaving original flood waters and their entrained sediments lagging increasingly farther behind with increasing distance downstream. This process can be modeled by routing the changes in discharge at the flood-wave celerity, while routing the sediments at the flow velocity. Testing of this model using data previously collected indicated that differences in flood-wave and flow velocity explain a large portion of the downstream variations in the relation of discharge to concentration through time. The routing model results suggests that one explanation of seasonal and storm-period variations in sediment rating curves may be seasonal changes in the distance to sediment sources.

Tsihrintzis (1995) stated that the primary function of a drainage culvert - to convey the design flow effectively - is often greatly impaired or lost due to deposited sediments. The effect of sediments on the total head loss within the culvert may be significant. A case study is presented that describes the performance of a roadway drainage culvert designed for clear-water flow conditions in an alluvial stream carrying sediments. The actual capacity of the culvert was approximately only 20% of the presumed design capacity, as a result of sediment deposition not accounted for in the design. The case study reviews design errors and demonstrates the necessity of sediment-transport calculations when designing roadway drainage culverts in ephemeral alluvial streams. Ignoring sediment transport may have adverse effects, including significant road and adjacent-property

flooding as well as continuous and costly maintenance problems. He concludes that it is more economical to undertake a complete sediment-transport study before design than to deal with continuous maintenance later.

Changes of sediment-yield rates from disturbed earth systems were considered by Schumm and Rea (1995) through time as they reflect evolutionary changes within a landscape. When a drainage basin is disturbed significantly by base-level, climatic, or tectonic change, sediment yields increase dramatically, but with no further disturbance they decline rapidly. These sediment-yield changes have been documented at all scales, from small experimental studies, to incised channels, to the Colorado River basin, and to the Himalaya Mountains. Thus, the shape of the sediment-yield curve can be used to estimate future sediment yields and to interpret past tectonic events.

A simple design aid is presented by Akan and Antoun (1994) for quickly sizing flood-control detention basins and outlet structures. The design objective is to control post development flood volume rather than peak discharge. Alternatively, the method can control downstream channel erosion caused by post development flows. The detention basins considered have a single outlet. The design aid is based on predetermined solutions to the reservoir-routing equation. To evaluate the channel-erosion tendencies, a generic bed-load formula is employed. All equations are written in dimensionless form, and solutions are obtained in terms of a set of governing dimensionless parameters. Results are generalized using hydrologic similarity and presented in chart form. These charts can be used to determine required stage-storage relationship for a detention basin and the size of the outlet structure.

Garbrecht et al. (1995) discussed a new sediment transport capacity algorithm for measuring large scale propagation and redistribution of sediments in channel networks. The method uses four established sediment transport equations to calculate transport capacity. The equal mobility characteristics of sediment mixtures is considered by modified critical shear stress. They showed that the algorithm generates consistent results for a wide range of flow and sediment characteristics.

GEOGRAPHICAL INFORMATION SYSTEMS AND MODELING

Uses of Geographical Information Systems to simplify data input have been considered recently. A computer algorithm to calculate USLE and RUSLE LS-factors over a two-dimensional landscape is presented by Desmet and Govers (1996). When compared to a manual input, both methods yield broadly similar results in terms of relative erosion risk mapping. There appear to be important differences in absolute values although both methods yield similar slope values. Use of the manual method leads to underestimation of erosion risk because of the effect of flow convergence. The computer procedure has the obvious advantage that it can easily be linked to GIS software. A comparison with

soil data showed a reasonably good agreement between predicted erosion risk and intensity of soil truncation in the test area. Another method that integrates geographic information systems and databases was developed by Mellerowicz et al. (1994) to aid in soil and water conservation planning. A map of polygons with combinations of Universal Soil Loss Equation factors was formed through integration of soil, climate and land use information. Manipulation of factors allowed evaluation of different scenarios that may occur in the watershed.

Garbrecht (1994) combined the geographic information system Arc/Info with the Agricultural Nonpoint Source Pollution Model (AGNPS) and proved that the sensitivity of water and sedimentation yield relates to size of the AGNPS grid. Delivery ratio, stream length and sediment yield were highly dependent on grid size. In-depth analysis of the input data and model results shows many inconsistencies that could affect findings and conclusions for a given application.

A geographic information system (GIS) interfaced with a geomorphic-based hydrologic and sediment transport model by Mashriqui and Cruise (1997) uses the "grouped response unit" concept whereby land classes are identified within homogeneous regions and used as hydrologic and sediment response units. The computational units are defined on the basis of homogeneity of topography and soil characteristics using frequency histograms of relevant parameters as objective criteria. The model is then applied to each land class within the computation units. The GIS/model interface is accomplished on an interactive basis in order to allow the user to have some decision-making authority. The methodology is demonstrated in detail and six years of runoff and sediment data are simulated.

URBAN DEVELOPMENT AND SEDIMENT CONTROL

Stream channel erosion has long been suspected as the major contributor to long-term sediment yield from urbanizing watersheds (Trimble, 1997). For San Diego Creek in southern California, measurements indicated that stream channel erosion furnished 105 megagrams per year of sediment, about two-thirds of the total sediment yield. Channel erosion can be a major source of sediment yield from urbanizing areas, and channel stabilization should be a priority in managing sediment yield.

Lange et al. (1996) suggest that the most effective efforts to control construction sediment usually focus on preventing the contaminants from ever reaching the storm drainage system. By far the most significant urban storm water contaminant is sediment. Construction activities are the chief culprit in increased sediment by providing areas where natural vegetative cover has been removed and bare soil is subject to the full erosive force of rainfall and runoff. The most cost effective technologies must be used.

Raghuwanshi et al. (1994) produced a model for an instantaneous-unit sediment graph (IUSG) based on attenuation and translation functions of mobilized sediment developed and applied to a Chaukhutia watershed (452.25 km²). An IUSG is a sediment graph resulting from one cm of mobilized sediment generated uniformly over the basin area during the effective rainfall of infinitesimally small duration. The catchment representative IUSG was converted into a unit sediment graph and convolved with mobilized sediment for generation and prediction of sediment graphs. The predicted sediment graphs showed good agreement with observed values except for lower peak sediment rates. Changes in hydrologic regime of the catchment due to adoption of conservation measures are mainly reflected by the attenuation of crest segments and peak sediment flowrates of IUSGs for the successive years.

PARTICLE SIZE AND SETTLING

Particle settling has long been recognized as an important aspect of water and wastewater treatment processes. Johnson et al. (1996) suggested that microbial aggregates generated by these processes are fractal and therefore, have different settling velocities. An investigation of the settling velocities of impermeable spherical aggregates generated from dyed latex micro spheres in standard paddle mixers shows that fractal aggregates settle about four to eight times faster than velocities predicted using an impermeable sphere model, also known as Stoke's law.

Meyer and Harmon (1992) recognized that sediment size characteristics, distribution and density should be considered in erosion assessments because they all affect sediment transport and deposition. Soil samples from 22 areas in Mississippi, Iowa and Alabama were studied for sediment characteristics. Researchers simulated rainstorms and collected data on erosion rate and sediment size. The data gathered were used to construct a model of soil and nutrient losses from agricultural lands.

A new and simplified formula for predicting the settling velocity of natural sediment particles was developed by Cheng (1997). His formula proposed a relationship between particle Reynolds number and a dimensionless particle parameter. It is applicable to a wide range of Reynolds numbers from the Stokes flow to the turbulent regime. The proposed formula has the highest degree of prediction accuracy when compared with other published formulas.

Water quality, metals concentration, and particle size distributions were characterized in urban runoff by Characklis and Wiesner (1997). Concentrations of particle number, organic carbon, suspended solids, iron, and zinc increased during storms. Data from two storms followed throughout their duration show individual materials eluting at different stages during storms. These measurements also indicated potential relationships between the zinc/organic carbon and iron/macrolloidpairs. Elevated contaminant concentrations

and increased flows during storms created loadings equal to weeks or months of background flow. Data showed no evidence of the "first flush" which has been observed in many smaller watersheds. Results may have implications for the design of large-scale storm-water management strategies.

Loss of sediments and nutrients from land surfaces to surface water supplies continues to be an important source of nonpoint source pollution according to Wall et al. (1996). The close relationship between loadings of suspended solids and total phosphorus has been reported in many studies. Wall et al.'s study sought to develop an empirical relationship between phosphorus and suspended solid loadings in the Canadian Great Lakes basin. Annual loadings of suspended solids and total phosphorus were collected from agricultural surface water quality studies carried out in Ontario. Various study factors such as plot, field, and watershed sizes, as well as methods, loadings, and references, were documented and annual loading values were plotted as the ratio of annual phosphorus/suspended solids loading versus the unit area suspended solids loading. The developed equation showed an exponential enrichment relationship of the phosphorus to suspended solids ratio with the unit area suspended solids loading, regardless of drainage area size. The equation enables a reasonable prediction of phosphorus loads for known sediment loadings.

Wu et al. (1993) used traditional techniques such as sieving, sedimentation and static and dynamic light scattering to estimate soil particle-size distributions across a broad range, from 5-cm to 20-nm radius. A power law $N \propto r^{-\nu}$ (super - ν), with the exponent $\nu = 2.8$ plus or minus 0.1, was observed in cases where the number of particles, N , per unit volume was present in a radius which was greater than r . Normally, more than twenty to fifty years of length scales were observed.

The matching of parameterized models with particle-size distribution was used to compare the jaky model, the standard lognormal model, two improvised lognormal models and the bimodal lognormal model, and examine them with mass-size data of 71 texturally varied New Zealand soils (Buchan et al., 1993). The standard lognormal model gave a worse fit to data for 23 soils, than the jaky model did for several soils. An improvised lognormal model, ORL and the bimodal model matched the data the best.

Analytical techniques applied to the definition of a particle are reviewed by Barth and Sun (1993). They involved the utilization of scattering techniques, size exclusion/hydrodynamic chromatography, field-flow fractionation electrozone sensing, sedimentation/centrifugation, sieving and other methods such as ultrasonics. They also compared the techniques in terms of particle shape and particle size standards. Haster and James (1994) presented a mathematical model representing washoff of sediments from small urban watersheds during storm events. The model simulates the contribution of sediments from each of the different land surfaces present within an urban watershed. They reasoned that different land surfaces contribute sediments differently, and that a better estimate of the total sediment load could be determined by representing

each of the major land surfaces independently. The model was developed and tested using water-quality data from four small urban watersheds in Houston and Austin, Tex., and by using data from bare-soil erosion plot studies. Performance of the model compared the simulated results with observed results during storm events that were analyzed. Given the appropriate parameters, the model provides reasonable estimates of the observed sediment yield from each of the different land surfaces studied. The rate at which sediments are washed off the impervious area of a watershed is shown to correlate with the length of time since rainfall has last occurred.

A study by Durnford and King (1993) consisted of rainfall-runoff events produced with a large rainfall simulator. Three test plots were 2.44 m wide, with lengths of 6.1 m, 13.72 m, and 24.38 m, and a slope of 2%. The soil on the plots was loamy sand. Rainfall intensities of 44 mm/h, 79 mm/h, and 160 mm/h were run for 1 h for each test. Samples of the runoff were analyzed for sediment particle-size distribution. Conclusions about the processes governing the erosion rates were that transport capacity tended to limit erosion rate of larger particles and supply limited the erosion rate of smaller particles. Data demonstrated that evaluating a single detachment or transport rate and assuming it to be constant for a season, or even a storm, may not always produce accurate results. Variations of these rates, due to armoring, must be taken into consideration.

Daniels and Gilliam (1996) found that vegetated filter strips help reduce non-point source pollution from agricultural areas. Even though such vegetation is an accepted and highly promoted practice, little quantitative data exist on its effectiveness under field conditions. The objective of this research was to determine the amount of nutrients and sediment removed by natural and planted filters. This was achieved by collecting and analyzing runoff at field edges and at various locations in vegetated buffers. Total weight of sediment and nutrients in runoff from North Carolina agricultural fields showed that the grass and riparian filter strips studied reduced runoff load by 50 to 80%. Total sediment decrease through the filters was about 80% for both grass and riparian vegetation.

TURBIDITY

Turbidity can be effectively used as an indicator of total phosphorus and suspended solids concentrations in streams (Grayson et al., 1996). Data collected from a 5000 square km catchment revealed the utility of the turbidity parameter in continuous measurement of containment loads. Field turbidity measurements largely overcome the disadvantages of conventional common flow based methods. However, they believe attitudinal changes must precede the induction of site specific estimations as a routine feature of monitoring containment loads.

Siano (1993) developed a simple method to correct for primary light scattered forward to the detector in turbidity measurements of Rayleigh scatters. The relative measurement error is shown to be independent of turbidity and specific absorbance, unlike the error calculated by use of a more involved model. In addition, although both methods consider absorbing components in the sample, only the simple method can be used when absorbing components and/or scattering components of any size are present in the blank.

Present knowledge regarding associations between sediment and riverine aquatic habitat is summarized in ASCE (1992). This article reports that engineering approaches can be used to evaluate and predict aquatic-habitat conditions, but as the grain size distribution of the bedload approaches that of the bed material, the number of benthic species declines. Sediments provide cover and spawning sites for fish and habitat for fish and food organisms. Sediment also serves as an indirect indicator of habitat quality. Major environmental issues associated with sediment transport in rivers include transport of organic sediments, sediment-water-quality interactions, deposition of sediments finer than gravel on and within coarser deposits, and filling of low-velocity areas contiguous to major river channels. It is noted that most stream organisms can withstand short-term exposure to elevated levels of suspended sediment, but chronic exposure is more detrimental.

Turbidity results from suspended material including clay and other sediment, algae, organic matter, and bacteria. The term is used to define the degree to which light is scattered and absorbed instead of passing through a water sample. Various studies have either measured turbidity at specific times and locations or have tried to relate turbidity to other contaminants. In this section, primary focus is on relating turbidity to suspended solids.

Turbidity relationships with fish survivability has been studied by various researchers. A study by Barnes, et al. (1996) analyzed existing fish and sediment data by comparing suspended sediment as measured by turbidity (NTU) with fish characteristics. They concluded that in the Piedmont, native fishes could be protected if random monthly samples of turbidity never exceed 100 NTU or less than 20 percent of samples exceed 25 NTU.

A field and modeling study by Sturm and Kirby (1991) evaluated the design criteria and best management practices for controlling sediment from construction sites. They utilized field data from landfill sites with sediment basins and compared TSS and NTU relationships. Rainfall, watershed hydrology and size, soil properties and conservation measures, and the sediment basin design were all found to impact whether desired turbidity limits were exceeded. A significant conclusion was the importance of applying soil conservation practices to prevent sediment from reaching the sediment basin.

A separate study by the Gwinnett County Department of Public Utilities (1993) conducted sampling at three sites with varying degrees of erosion control for approximately four months. Considerable variations in the NTU versus TSS measurements were observed. For example at site 3 on August 27, Bottle 1 had a turbidity of 1230 NTU and TSS of 150 mg/l while Bottle 1 on September 21 had a turbidity of 78 NTU and TSS of 492 mg/l. Again, this shows that while an one-to-one relationship between turbidity and TSS can be assumed, there is tremendous variability between samples and the direct relationship may be an inverse relationship for specific samples.

The Georgia Board of Regents' Scientific Panel (1995) discussed the relationship between turbidity and suspended solids. They recognized that while a relationship can often be established between turbidity (NTU) and total suspended solids (TSS), the relationship can vary over a wide range as a function of location, time, stream energy, and sediment composition. They particularly noted that TSS and NTU levels may differ substantially and significantly. They concluded that, in the absence of better information about specific watersheds, a 1:1 relationship be assumed. Such a relationship was plotted for 1991 U.S. Geological Survey data for Georgia for suspended solids levels up to about 150 mg/l. Variation in the turbidity level was often one order of magnitude at a specific TSS level. It should be noted also that 150 mg/l is a relatively low TSS level compared to what frequently has been detected from construction sites.

A fact sheet by the Big Creek Project Technical Advisory Committee (1996) also considered the relationship between NTU and TSS. Measured values were compared at different stream levels. They indicated that statistical comparison of turbidity and total suspended solids shows a nearly one-to-one relationship using a logarithmic plot of the measurements. Measured values reached as high as 7000 mg/l with typical values between 300-800 NTU. Very few samples were less than 80 NTU.

A study of silvicultural practices (Green and Rasmussen, 1996) described efforts to relate turbidity in streams to BMP usage. Monitoring stations located up and down stream of forest practices were used to quantify the magnitude of turbidity changes. They concluded that while forest harvesting operations caused no significant long-term increase in average turbidities, turbidities can be affected by practices at individual sites. This was particularly evident for perennial streams under high flow in erodible soils of the Piedmont. Emphasis in this study was on long-term effects and not on direct effects during harvesting when there is increased potential for high erosion rates.

COST EFFECTIVENESS

Walker et al. (1993) studied average cost efficiency technique for quality control of water that is degraded by sediments in irrigation return flows and applied marginal

analysis that considers change in cost per unit in sediment reduction. A cost efficiency frontier is used for acquiring alternative levels of sediment control. They found that preventive methods for controlling erosion are not as cost effective as practices that clean up runoff.

The long-run cost of erosion to a farmer is incorporated in a damage function which is applied to evaluate conservation tillage in a model by Walker and Young (1986). The model was evaluated for four alternative rates of technological change affecting wheat yields and for the mean discount rate of each group under the four rates of technological change. Higher anticipated rates of multiplicative technological progress increase future damage from erosion, accelerate projected adoption of conservation tillage and encourage conservation of topsoil. Results such as these have policy implications for the control of erosion.

Epp and Hamlett (1996) evaluated changes in field costs and revenues with seven conservation best management practices (BMP) and two nutrient management programs (NMP) for three sites in the Susquehanna River Basin in Pennsylvania. Field layouts, rotation selection, BMP design, and CREAMS modeling of sediment and nutrient losses were reported. BMP implementation costs, field operation costs, and crop revenues were calculated with each BMP as well as the baseline condition representing present practices. The BMP/NMP combinations are compared for cost-effectiveness in reducing sediment, nitrogen, and phosphorus losses. Nonstructural BMPs (no-till, contour, contour with waterways, strip crop with waterways, filter strips) produced less reduction in net field income than did structural BMPs (terraces with waterways, parallel tile outlet terraces, sediment basins).

A nonpoint pollution control model to check monitoring problems in cases of dispersed pollution is proposed by Miljkovic (1995). The model acknowledges the inter-connection between policy makers, economic influences, and aims to promote environmental quality. A tax or subsidy incentive is used to attract polluting firms to an optimal abatement level, which preserves industries' incentives while providing government with additional income. Details of decision making processes by the government regulator and agent, a suspected polluter, are discussed

SCREENING FOR NEEDED MODEL CAPABILITIES

Screening of the models was accomplished using a three-level screening process. Level I screening was a simple determination of whether or not the model addresses stormwater, sediment, and sediment size distribution. Level II screening was used on those models that passed the first level to determine if the sediment modeling procedure was sufficiently detailed to allow the appropriate prediction of sediment yield and impact of erosion prevention and sediment control. Finally, Level III screening was simply a comparison of the capabilities of the four models that passed the first two levels of

screening. Based on the comparisons in Level III, recommendations are made on a model to be used.

LEVEL I SCREENING - GENERAL STORMWATER, SEDIMENT, AND SEDIMENT SIZE

Stormwater prediction - Turbidity results from erosive forces of rainfall and stormwater runoff, hence the need to predict stormwater discharge.

Sediment prediction - Turbidity is related to sediment concentration, hence the need to predict sediment production. It is important to recognize that some models (i.e., RUSLE) require the user to estimate a delivery ratio in order to estimate sediment yield. This is a significant disadvantage and is difficult to handle from a user viewpoint. Such models are not included in the Level II Screening.

Sediment size distribution - the performance of all sediment control measures is related to size distribution, hence the need to predict size distribution.

LEVEL II SCREENING - GENERAL SEDIMENT COMPUTATION REQUIREMENTS

Sediment yield/delivery ratio - Mere computation of erosion is not sufficient to estimate turbidity in a stream or reservoir. The quantity of sediment delivered to the channel must be calculated, which requires either a delivery ratio or computation of transport capacity. Some of the models use delivery ratio as input. However, delivery ratios are complex functions of parameters such as velocity, sediment size, transport capacity, etc., thus estimation is not simple. In order to have a reliable estimation procedure that is semi-independent of modeler expertise, a reliable procedure for estimating sediment yield should be included as part of the model computational procedure, not as an input parameter.

Erosion prevention (on-site) - The first line of defense for controlling erosion and turbidity is on-site control. Once suspended, sediment is difficult to remove, particularly the finer particle sizes. On-site controls protect soil from the erosive power of rainfall and flowing water. Techniques for evaluating the impact of on-site controls are thus necessary.

Erosion control (off-site)

- Retention/detention/ponds - The most commonly used technique for controlling sediment off-site is some form of impoundment. These

structures retain sediment for a period to allow particles to settle from the flow. The trapping efficiency varies widely, depending on outflow structure, surface area, and settling velocities. Accurate evaluation of the impact of impoundments is essential to developing proper control techniques.

- Small controls - Small controls are widely used as part of sediment control plans. Their effectiveness depends on the type of structure, porosity (slurry flow rate), and location (overland flow or channel flow control). A model to evaluate the impact of these structures is important.

LEVEL III SCREENING - SPECIFIC PREDICTION TECHNOLOGY REQUIREMENTS

Type simulation

- Single storm - Most design is based on single event predictions, hence the need to predict single events.
- Multiple storm - In addition to single storm events, it is sometimes advantageous to predict turbidity over a period of days to months. When that information is needed, routines will need to be developed to utilize the single event models to develop such predictions.

Predict sediment discharge

- Rill and interrill - Erosion from rills and interrill areas can be the primary source of sediment in construction areas when exposed areas have not been stabilized, thus models should have rill and interrill prediction capability.
- Concentrated flow - Flow in concentrated channels is a common occurrence on construction sites. It occurs when flow moves to convergence zones, prior to entering a defined stream. Such flows can be major sediment sources. In stabilized (vegetated) watersheds, channelized flow can be the primary source of sediment, thus it is important to have this computational capability built into the model.
- Predict turbidity - The project is focused on turbidity as the measure of impact of urbanization on stream water quality. The model selected must

be capable of predicting parameters that can be used to estimate turbidity, or must be modified to predict turbidity itself.

Hydraulic computations

- Variable time step to allow for small storage/large discharge - Flow controls such as culverts and inlets on urbanized watersheds will frequently create small impoundments and trap the coarser sediments. In these controls, outflow rates are typically nearly as large as the inflow rate and the storage volume is small, giving rise to unstable hydraulic routing predictions unless computational step size is extremely small. Such small step sizes are impractical for all calculations, hence results from fixed time step models frequently show outflow rates exceeding inflow rates, a physical impossibility. Thus, accurate estimation of the impact of these small controls is difficult to estimate unless the model being used has a variable time step. These variable time steps are employed when computed flow rates start changing rapidly.
- Continuous functions for stage discharge and area - Frequently, stage-discharge and stage-area information is utilized at discrete stage points and linear interpolation is utilized for values in between. Where discharge values change abruptly as flow transitions from one type of outlet to another (i.e., weir flow control to open channel flow control), serious errors can result in routing computation. This problem can be overcome by using continuous functions for stage-discharge and stage-area.
- Drop inlet - A commonly used outlet control device.
- Perforated risers - A commonly used outlet control device.
- Perforated risers with rock fill wrapping - An outlet control device which is sometimes used to prevent large sediment particles from clogging dewatering devices.
- Culvert outlets - A common flow control device.
- Open channel spillways - with control section - A frequently used emergency spillway type which can also be used as a principal spillway.
- Open channel spillways - without control section - A frequently used emergency spillway type which can also be used as a principal spillway.

Evaluate impact of small controls

- Rock fill checkdam - A commonly used small control, typically employed in ditches during construction.
- Filter fence - One of the most commonly used control techniques in overland flow control.
- Straw bales - A commonly used control technique in overland flow control.
- Inlet filters - A technique commonly used to protect storm sewer inlets during construction.

Evaluate impact of on-site controls (erosion prevention)

- Mulch (varying types) - A commonly used protection mechanism.
- Vegetated cover - A commonly used method of stabilizing bare soil, both temporary as well as permanent.
- Timing of establishment of vegetation - Timing of vegetal establishment is critical to erosion control.
- Geotextile blankets and netting - Frequently used in place of natural mulch or to hold mulch in place.
- Channel bank stabilization - Finding increasing use in stabilizing concentrated flow areas and channelized flow.
- Grade control structures - Used in channelized flow to prevent channel erosion.

Account for instream flow above and below discharge point - Based on current regulations, it will be necessary to output values that will allow computation of the impact of discharge on the turbidity of the receiving stream, showing how the turbidity downstream is changed from the turbidity upstream.

History of use on urban watersheds - Many erosion and sediment models have been developed primarily for evaluating agricultural and silvicultural operations. These models may not be readily adaptable to urban conditions, due to the nature of the difference in drainage structures.

Economic analysis capability - As one of the final products of this project, an analysis of the cost of the EP and SC systems must be made in order to select the system which has

least total cost to the developer and society in general while meeting the turbidity standards under design conditions. Thus, the output of the model must be in a form such that these computations can be readily made.

SALIENT POINTS ABOUT PREDICTION CAPABILITIES NOT CURRENTLY AVAILABLE IN ANY MODEL

Turbidity

Since turbidity has been identified by the RFP as the critical parameter for this project relating sediment to ecological impacts, it is important that turbidity predictions be modeled as accurately as possible. No current model includes turbidity as an output parameter, but the models that have been suggested as alternatives all predict sediment concentrations and sediment size distributions as output information. It has been suggested that turbidity can be related by simple regression relations to TSS, particularly for the finer portion. In a study of individual soil series, Rogers and Blalock (1991) indicate that for an individual soil horizon, 88-99% of the variability in turbidity can be explained by the TSS. For samples of more than one horizon, 81-91% of the variability in turbidity can be explained with mean errors varying between 22-32% for these composite analyses. Data further suggest that turbidity in NTU's can be estimated using a power function of the form, $NTU = aTSS^b$, where a and b are regression coefficients and TSS is total suspended solids in mg/l. Considerable variation was observed between both the field and laboratory values of "a and b," i.e., regression coefficients for "a" ranged from 1.84-107. This suggests that simple linear regression is not generally desirable, particularly for watersheds with multiple soil series where primary source areas may vary from storm to storm because of construction scheduling, etc.

The bottom line on this is that accurate computation of turbidity from suspended solids will require a more physically based relationship that accounts for the optical properties of sediment as well as the quantity of sediment.

Economics

An optimal analysis of the cost of the EP and SC systems must be made in order to select the system which has least total cost to the developer and society in general while meeting the turbidity standards under design conditions. Thus, the output of the model must be in a form such that these computations can be readily made. These may require some modification of the currently available model outputs.

RECOMMENDATIONS

After considering the characteristics of all the models surveyed, the following conclusions were reached about their overall capabilities:

1. SEDIMOT III is the most current model in terms of computational capability, stability of predictions, utilization of appropriate prediction technology for erosion prevention and sediment control, and variety of control technologies which can be evaluated. It is consistent with many of the routines employed by the latest and most sophisticated watershed hydrology and sedimentology model known as WEPP, but does not employ the rectangular hydrograph and sedimentgraph simplifications utilized in WEPP for ease of computation. It employs the much improved WEPP hydraulic routines for outlet structures and hydraulic routing but maintains the needed complexity of CSTRS utilized in SEDIMOT II and SEDCAD. A channel erosion routine has been employed utilizing a modification of the WEPP technology that can be utilized to predict concentrated flow erosion, a major component of sediment yield in many watersheds experiencing construction activity. Finally, it employs a more physically-based sedimentation procedure for small controls that were not available when SEDIMOT II and SEDCAD were developed. The major drawback to SEDIMOT III is the lack of a user-friendly interface. A Windows 95-based interface is currently being developed with version 1.0 nearing completion. If SEDIMOT III is utilized for this project, evaluation and modification of the interface will need to be a part of the activity. Modifications will need to be made to the model to predict turbidity and economics. Model inputs are very similar to SEDIMOT II and SEDCAD+ which have been widely applied to urban watersheds undergoing construction. Thus users should not have difficulty generating the inputs. The model was used to develop the Design Aids utilized in South Carolina.
2. SEDCAD+, V3 has the best developed user interface currently available. The current DOS version allows the user to utilize a number of peripheral devices such as digitizers, plotters, and printers. Routines have been included to allow the user to more easily input slopes, areas, slope lengths, volumes, etc. Utilities are available to design stable channels and outlet protection. The computational procedures in the model are essentially those of SEDIMOT II, with their inherent limitations, including fixed time steps, discrete stage area and stage discharge inputs, and limited built-in capability for evaluation of small controls. Evaluation of concentrated flow erosion is not a possibility for the model. In addition, the calculation of sediment deposition between structures is based on the MUSLE routine, which is not widely accepted. The model will need to be modified to predict turbidity and evaluate economics. The model has been widely used for urban watersheds undergoing construction.

3. SEDIMOT II has the same basic problems that are present in SEDCAD. In addition, it has a user interface that is acceptable, but not as sophisticated as SEDCAD. If used on this project, it will need to be modified to predict turbidity and to evaluate economics. The model has been widely used for urban watersheds undergoing construction.
4. WEPP is the model developed to replace the Universal Soil Loss Equation and watershed hydrology and sedimentology models used by the NRCS. The model is a very sophisticated continuous simulation model that can evaluate hillslope erosion and route sediment through to reservoirs and sediment control structures. The hydraulic routines are state of the art as are the hydrologic procedures. Since the model uses continuous simulation, simplification of the hydraulic and sediment routing procedures were made to facilitate computational speed including the assumption of rectangular hydrographs and sedimentgraphs. Sediment routing procedures were simplified as well to a single reactor model. The procedures are primarily focused on agricultural production operations and require an extensive database for input. The user interface is somewhat cumbersome. The model could be utilized for urban watersheds but there is no experience in its use for this purpose. It would need to be evaluated for urban areas and modified to predict turbidity and to evaluate economics.

REFERENCES CITED

Akan, A. O. and E. N. Antoun. 1994. Runoff detention for flood volume or erosion control. *Journal of Irrigation and Drainage Engineering* Jan-Feb v120 n1 p168(11).

Arnolds, J. G., J. R. Williams and D. R. Maidment. 1995. Continuous-time water and sediment-routing model for large basins. *Journal of Hydraulic Engineering* Feb v121 n2 p171(13).

ASCE. 1992. Sediment and aquatic habitat in river systems. (relationship between sediment transport and river ecology) *Journal of Hydraulic Engineering* May v118 n5 p669(19).

Barnes, K. H., Meyer, J. L., and Freeman, B. J. 1996. Suspended sediments and Georgia's Fishes: An analysis of existing information. Institute of Ecology, University of Georgia, Athen, GA, 61 pp.

Barth, H.G. and S. Sun. 1993. Particle size analysis. *Analytical Chemistry* June 15 v65 n12 p55R(12).

Big Creek Project Technical Advisory Committee. 1996. Effects of soil erosion in the Big Creek watershed. Upper Chattahoochee Riverkeeper. Fact Sheet, 4 pp.

Bouraoui, F. and T. A. Dillaha. 1996. ANSWERS-2000: runoff and sediment transport model. *Journal of Environmental Engineering* June v122 n6 p493 (10).

Buchan, G. D., K. S. Grewal and A. B. Robson. 1993. Improved models of particle-size distribution: an illustration of model comparison techniques. *Soil Science Society of America Journal* July-August v57 n4 p901(8).

Cerco, C. F. and T. Cole. 1993. Three-dimensional eutrophication model of Chesapeake Bay. *Journal of Environmental Engineering* Nov-Dec v119 n6 p1006(20).

Cheng, N. 1997. Simplified settling velocity formula for sediment particle. *Journal of Hydraulic Engineering* Feb v123 n2 p149(4).

Cooper, A. B. and A. B. Bottcher. 1993. Basin-scale modeling as tool for water-resource planning. *Journal of Water Resources Planning and Management* May-June v119 n3 p306(18).

Daniels, R. B. and J.W. Gilliam. 1996. Sediment and chemical load reduction by grass and riparian filters. *Soil Science Society of America Journal* Jan-Feb v60 n1 p246(6).

Desmet, P. J. J. and G. Govers. 1996. A GIS procedure for automatically calculating the USLE LS factor on topographically complex landscape units. *Journal of Soil and Water Conservation* Sep-Oct v51 n5 p427(7).

Durnford, D. and J. P. King. 1993. Experimental study of processes and particle-size distributions of eroded soil. *Journal of Irrigation and Drainage Engineering* March-April v119 n2 p383(16).

Epp, D.J. and J.M. Hamlett. 1996. Cost-effectiveness of conservation and nutrient management practices in Pennsylvania. *Journal of Soil and Water Conservation* Nov-Dec v51 n6 p486(9).

Garbrecht, J. 1994. Nonpoint-pollution model sensitivity to grid-cell size. *Journal of Water Resources Planning and Management* Sept-Oct v120 n5 p738(5).

Garbrecht, J., R. Kuhnle and C. Alonso. 1995. A sediment transport capacity formulation for application to large channel networks. *Journal of Soil and Water Conservation* Sept-Oct v50 n5 p527(3).

Georgia Board of Regents' Scientific Panel. 1995. Erosion and sedimentation: Scientific and Regulatory Issues. Georgia Board of Regents' Scientific Panel on Evaluating the Erosion Measurement Standard, University of Georgia, Athens, GA, 34 pp.

Grayson, R.B., B.L. Finlayson, C.J. Gippel and B.T. Hart. 1996. The potential of field turbidity measurements for the computation of total phosphorus and suspended solids loads. *Journal of Environmental Management* July v47 n3 p257(11).

Green, F. and Rasmussen, T. 1996. The effects of silvicultural practices on water quality in Georgia: A study of turbidity. Georgia Environmental Protection Division of Georgia DNR. Athen, GA.

Gwinnett County Department of Public Utilities. 1993. Preliminary report sediment monitoring at three sites. Draft, Sampling and Results, 93001-5, Construction Engineering Division, Storm Water Management Program, Gwinnet County, GA.

Haster, T. W. and W. P. James. 1994. Predicting sediment yield in storm-water runoff from urban areas. *Journal of Water Resources Planning and Management* Sept-Oct v120 n5 p630(21).

Johnson, C. P., X. Li and B. E. Logan. 1996. Settling velocities of fractal aggregates. *Environmental Science & Technology* June v30 n6 p1911(8).

Kothyari, U.C., A.K. Tiwari and Ranvir Singh. 1994. Prediction of sediment yield. *Journal of Irrigation and Drainage Engineering* Nov-Dec v120 n6 p1122(10).

Laflen, J. M. 1997. WEPP - erosion prediction for the next millenium. (Water Erosion Prediction Project). *Agricultural Research* April v45 n4 p2(1).

Laflen, J.M., W.J. Elliot, D.C. Flanagan, C.R. Meyer, and M.A. Nearing. 1997. WEPP-predicting water erosion using a process-based model. (computer model for predicting soil erosion). *Journal of Soil and Water Conservation* March-April v52 n2 p96(7).

Lange, L., H. Andrews and K. Kisinger. 1996. 10 issues in urban stormwater pollution control. *American City & County* Sep v111 n10 p36(8).

Marcus, W. A. 1989. Lag-time routing of suspended sediment concentrations during unsteady flow. *The Geological Society of America Bulletin* May v101 n5 p644(16).

Mashriqui, H.S. and J.F. Cruise. 1997. Sediment yield modeling by grouped response units. *Journal of Water Resources Planning and Management* March-April v123 n2 p95(10).

Melching, C. S. And C. G. Yoon. 1996. Key sources of uncertainty in QUAL2E Model of Passaic River. *Journal of Water Resources Planning and Management* March-April v122 n2 p105(9).

Menendez, A. 1997. Sedimentologic modeling selection based on study scale. *Journal of Hydraulic Engineering* Oct v123 n10 p922(4).

Meyer, L. D. and W.C. Harmon. 1992. Size characteristics of sediment from agricultural soils. *Journal of Soil and Water Conservation* Jan-Feb v47 n1 p107(5).

Miljkovic, D. 1995. Decision making process in a nonpoint pollution control model. *Journal of Environmental Management* Nov v45 n3 p255(8).

Nearing, A., J. Williams, E. Skidmore, C. Valentin, K. King and R. Savabi. 1996. Using soil erosion models for global change studies. *Journal of Soil and Water Conservation* Sep-Oct v51 n5 p381(5).

NYS. 1994. Predicting pollutant loading through the use of models. NYS Department of Environmental Conservation and the NYS Soil and Water Conservation Committee. November. 28pp.

Schumm, S. A. and D. K. Rea. 1995. Sediment yield from disturbed earth systems. *Geology* May v23 n5 p391(4).

Scott, T. 1996. City preaches, practices stormwater management. *American City & County* Sep v111 n10 p42(1).

Sharma, P.P., S.C. Gupta and G.R. Foster. 1995. Raindrop-induced soil detachment and sediment transport from Interrill areas. *Soil Science Society of America Journal* May-June v59 n3 p727(8).

Smith, R.E., D.C. Goodrich and J.N. Quinton. 1995. Dynamic, distributed simulation of watershed erosion: the KINEROS2 and EUROSEM models. *Journal of Soil and Water Conservation* Sept-Oct v50 n5 p517(4).

Solo-Gabriele, H. M. and F. E. Perkins. 1997. Metal transport within a small urbanized watershed. *Journal of Irrigation and Drainage Engineering* March-April v123 n2 p114(9).

Solo-Gabriele, H. M. and F. E. Perkins. 1997. Watershed-specific model for streamflow, sediment, and metal transport. *Journal of Environmental Engineering* Jan v123 n1 p61(10)

Trimble, S. W. 1997. Contribution of stream channel erosion to sediment yield from an urbanizing watershed. *Science* Nov 21 v278 n5342 p1442(3).

Tsihrintzis, V. A. 1995. Effects of sediment on drainage-culvert serviceability. *Journal of Performance of Constructed Facilities* August v9 n3 p172(12).

Velleux, M., J. Gailani and D. Endicott. 1996. Screening-level approach for estimating contaminant export from tributaries. *Journal of Environmental Engineering* June v122 n6 p503(12).

Wall, G.J., A.W. Bos and A.H. Marshall. 1996. The relationship between phosphorus and suspended sediment loads in Ontario watersheds. *Journal of Soil and Water Conservation* Nov-Dec v51 n6 p504(4).

Wu, J. S., R. E. Holman and J. R. Dorney. 1996. Systematic evaluation of pollutant removal by urban wet detention ponds. *Journal of Environmental Engineering* Nov v122 n11 p983(6).

Ziegler, C. K. and B. Nisbet. 1994. Fine-grained sediment transport in Pawtuxet River, Rhode Island. *Journal of Hydraulic Engineering* May v120 n5 p561(16).

Raghuwanshi, N. W., R.A. Rastogi and Santosh Kumar. 1994. Instantaneous-unit sediment graph. *Journal of Hydraulic Engineering* April v120 n4 p495(9).

Walker, J. F. 1994. Statistical techniques for assessing water-quality effects of BMPs. (best management practices) *Journal of Irrigation and Drainage Engineering* March-April v120 n2 p334(14).

Siano, S. 1993. A simple method of correction for forward Rayleigh scattering in turbidity measurements. *Applied Optics* August 20 v32 n24 p4646(6).

Srivastava, R. and D.N. Contractor. 1992. Bed-load and suspended-load transport of nonuniform sediments. *Journal of Hydraulic Engineering* June v118 n6 p948(3).

Sturm, T. W. and Kirby, R. E., Jr. 1991. Sediment reduction in urban stormwater runoff from construction sites. Technical Completion Report ERC 04-91, Environmental Resources Center, Georgia Institute of Technology. Atlanta, GA. 103 pp.

Walker, D. J. and D. L. Young. 1986. The effect of technical progress on erosion damage and economic incentives for soil conservation. *Land Economics* Feb v62 n1 p83(11).

Walker, D. J., B. L. Calkins and J. R. Hamilton. 1993. Marginal cost effectiveness analysis for agricultural nonpoint source water quality control. *Journal of Soil and Water Conservation* July-August v48 n4 p368(5).

Wu, Q., M. Borkovec and H. Sticher. 1993. On particle-size distributions in soils. *Soil Science Society of America Journal* July-August v57 n4 p883(8).

Wu, T. H., J. A. Hall and J. V. Bonta. 1993. Evaluation of runoff and erosion models. *Journal of Irrigation and Drainage Engineering* March-April v119 n2 p364(19).

APPENDIX - ADDITIONAL REFERENCES

GOVERNMENT REFERENCES

Influences of environmental settings on aquatic ecosystems in the Apalachicola - Chattahoochee - Flint River basin 1.1996. Geological Survey (U.S.) 119.42/4:95-4278.

Soil survey of Chattahoochee and Marion counties, Georgia [1997] United States. A 57.38/10:C 39.

Effect of the restricted use of phosphate detergent and upgraded wastewater-treatment facilities of water quality in the Chattahoochee River near Atlanta, Georgia. Microfiche. 1994. Geological Survey, (U.S.) 119.76:94-99.

Nutrient sources and analysis of nutrient water-quality data, Apalachicola - Chattahoochee - Flint River basin, Georgia, Alabama, and Florida, 1972-90 /. 1996. Geological Survey (U.S.) 119.42/4:96-4101.

Base-flow characteristics of streams in the Valley and Ridge, Blue Ridge, and Piedmont physiographic provinces of Virginia I. [1997] Geological Survey (U.S.) 119.13:2457.

Quality assurance plan for the collection and processing of sediment data by the U.S. Geological Survey, Water Resources Division. Microfiche. 1993. Geological Survey (U.S.) 119.76:92-499.

Design manual for sedimentation control through sedimentation ponds and other physical/chemical treatment I. [1982] Simons, Li Associates. I 71.4:SE 2.

Economic costs and benefits associated with investments in pollution prevention structures. Microfiche. [1995] Environmental Research Center (Tennessee Valley Authority) Y 3.T 25:4/Z-362.

A summary of best management practices for nonpoint source pollution. Microfiche. 1994. Construction Engineering Research Laboratories (U.S.) D 103.53:EP-93/06.

Stormwater pollution abatement technologies : project summary. Microfiche. 1994] Risk Reduction Engineering Laboratory (U.S.) EP 1.89/2 :600/SR-94/1 29.

Urban runoff pollution prevention and control planning. Microfiche. [1993] Center for Environmental Research Information (U.S.) EP T.8:UR 1.

Stormwater pollution abatement technologies. Microfiche. [1994] Risk Reduction Engineering Laboratory (U.S.) EP 1.23/6:600/R-94/1 29.

Guidance manual for developing best management practices (BMP). Microfiche. 1994. United States. EP 2.8:B 46.

Best management practices for erosion and sediment control. Microfiche. [1995] United States. TD 2.30/17:94-005.

World Wide Web access to publications and data for the Apalachicola - Chattahoochee - Flint River Basin, Georgia, Florida, and Alabama, 1992-95 /. [1997]. Geological Survey (U.S.). 119.127:78-97

Predicting soil erosion by water : a guide to conservation planning with the revised universal. [1997] United States. A 1.76:703. GPO stock no.: 001-000-04636-5.

Construction site, soil erosion and sediment control. [1997] United States. A 57.2:SE 2/7.

Streambank erosion study inventory, Rifle River/. [1994] United States. A 57.68:R 44/SH.1-17.

Chesapeake Bay watershed, highly erodible land on cropland, 1992/. 1994] United States. A 57.68:N I 9/992/PACK.

Simulation models, GIS and nonpoint-source pollution : January 1991 - December 1993.1994. National Agricultural Library (U.S.) A 17.18/4:94-06.

A primer for financial analysis of pollution prevention projects. Microfiche. 1993. Risk Reduction Engineering Laboratory (U.S.) EP 1.23/6:600/R-93/059.

Predicting soil erosion by water : a guide to conservation planning with the revised universal. [1997] United States. A 1.76:703. GPO stock no.: 001-000-04636-5.

Construction site, soil erosion and sediment control. [1997] United States. A 57.2:SE 2/7..

Streambank erosion study inventory, Rifle River. [1994] United States. A 57.68:R 44/SH.1-17.

Chesapeake Bay watershed, highly erodible land on cropland, 1992/. 1994] United States. A 57.68:N I 9/992/PACK.

United States Department of Agriculture. 1976. Soil survey of Coweta, Heard, and Troup Counties, Georgia. USDA-SCS, 102 pp., illus.

United States Department of Agriculture. 1965. Soil survey Meriwether County, Georgia. Series 1961, No. 15.

United States Department of Agriculture. 1961. Soil survey Douglas County, Georgia. Series 1959, No. 1. (Supplement issued in 1982)

United States Department of Agriculture. 1967. Hydric soils with acreage for Gwinnett County, Georgia. (Supplement issued in 1988, updated in 1992)

United States Department of Agriculture. 1973. Soil survey of Cobb County, Georgia.

United States Department of Agriculture. 1971. Soil survey of Carroll and Haralson Counties, Georgia.

United States Department of Agriculture. 1982. Soil survey of Dekalb County, Georgia.

OTHER RELEVANT REFERENCES

1997

Numerical simulation of sheetflow as granular material. Hitoshi Gotoh, Tetsuo Sakai. Journal of Waterway, Port, Coastal and Ocean Engineering Nov-Dec 1997 v123 n6 p329(8).

Contribution of stream channel erosion to sediment yield from an urbanizing watershed. Stanley W. Trimble. Science Nov 21, 1997 v278 n5342 p1442(3).

Sedimentologic modeling selection based on study scale. Angel Menendez. Journal of Hydraulic Engineering Oct 1997 v123 n10 p922(4).

Sample size needs for characterizing pollutant concentrations in highway runoff. N.R. Thompson, E.A. McBean, W. Snodgrass, I. Mostrenko. Journal of Environmental Engineering Oct 1997 v123 n10 p1061(5).

Stopping erosion with gypsum and PAM. (polyacrylamide) Hank Becker. Agricultural Research Sep 1997 v45 n9 p18(3).

Streamflow and suspended sediment transport in an urban environment. Helena M. Solo-Gabriele, Frank E. Perkins. *Journal of Hydraulic Engineering* Sep 1997 v123 n9 p807(5).

Sediment Transport Theory and Practice. (book reviews) Carl F. Nordin Jr. *Journal of Hydraulic Engineering* Sep 1997 v123 n9 p833(3).

GIS to estimate storm-water pollutant mass loadings. (geographic information system) Kenneth M. Wong, Bric W. Strecker, Michael K. Stenstrom. *Journal of Environmental Engineering* August 1997 v123 n8 p737(9).

Effect of concentration on settling velocity of sediment particles. Nian-Sheng Cheng. *Journal of Hydraulic Engineering* August 1997 v123 n8 p728(4).

Computer-controlled variable intensity rain simulator. (Soil & Water Management & Conservation) R.J. Lascano, J.T. Vorheis, R.L. Baumhardt, D.R. Salisbury. *Soil Science Society of America Journal* July-August 1997 v61 n4 p1182(8).

Sediment characteristics and colonization of soft-bottom benthos: a field manipulation experiment. R.S.S. Wu, P.K.S. Shin. *Marine Biology* July 1997 v128 n3 p475(13).

Sediment-laden flow in open channels from two-phase flow viewpoint. (responses to Zhixian Cao, *Journal of Hydraulic Engineering*, vol.121, no.10, October 1995)(includes reply) H.O. Anwar, P.Y. Julien. *Journal of Hydraulic Engineering* June 1997 v123 n6 p577(4).

Experiments and model validation. (Erosion of Fluid Mud Layers, part 2) J.C. Winterwerp, C. Kranenburg. *Journal of Hydraulic Engineering* June 1997 v123 n6 p512(8).

Debris flow run-out and landslide sediment delivery model tests. J.C. Bathurst, A. Burton, T.J. Ward. *Journal of Hydraulic Engineering* May 1997 v123 n5 p410(10).

Coupled modelling of alluvial flows. Saied Saiedi. *Journal of Hydraulic Engineering* May 1997 v123 n5 p440(7).

Design of single-chamber settling basins. Nandana Vittal, Mavendra Singh Raghau. *Journal of Hydraulic Engineering* May 1997 v123 n5 p469(3).

Stream channel erosion and change resulting from riparian forests. Stanley W. Trimble. *Geology* May 1997 v25 n5 p467(3).

WEPP - erosion prediction for the next millenium. (Water Erosion Prediction Project)
John M. Laflen. Agricultural Research April 1997 v45 n4 p2(1).

Experimental simulation of channel incision into a cohesive substrate at varying
gradients. Ellen Wohl, Hiroshi Ikeda. Geology April 1997 v25 n4 p295(4).

The role of severe storms in soil erosion: a problem needing consideration. W.E. Larson,
M.J. Lindstrom, T.E. Schumaker. Journal of Soil and Water Conservation March-April
1997 v52 n2 p90(6).

Soil erosion effects on soil properties in a highland area of central Kenya. C.K.K.
Gachene, N.J. Jarvis, H. Linner, J.P. Mbuvi. Soil Science Society of America Journal
March-April 1997 v61 n2 p559(6).

WEPP-predicting water erosion using a process-based model. (computer model for
predicting soil erosion) J.M. Laflen, W.J. Elliot, D.C. Flanagan, C.R. Meyer, M.A.
Nearing. Journal of Soil and Water Conservation March-April 1997 v52 n2 p96(7).

Sediment yield modeling by grouped response units. H.S. Mashriqui, J.F. Cruise.
Journal of Water Resources Planning and Management March-April 1997 v123 n2
p95(10).

Metal transport within a small urbanized watershed. Helena M Solo-Gabriele, Frank E.
Perkins. Journal of Irrigation and Drainage Engineering March-April 1997 v123 n2
p114(9).

Analysis of fine-grained sediment movement in small canals. Panagiotis D. Scarlatos, Lin
Li. Journal of Hydraulic Engineering March 1997 v123 n3 p200(8).

Turbulent bursting-based sediment entrainment function. Zhixian Cao. Journal of
Hydraulic Engineering March 1997 v123 n3 p233(4).

Simplified settling velocity formula for sediment particle. Nian-Sheng Cheng. Journal of
Hydraulic Engineering Feb 1997 v123 n2 p149(4).

Proposed sediment contamination guidelines to look at chemical mixtures. Rebecca
Renner. Environmental Science & Technology Feb 1997 v31 n2 p80A(2).

Stable width of an alluvial channel. Mohammad N. Cheema, Miguel A. Marino, Johannes
J. DeVries. Journal of Irrigation and Drainage Engineering Jan-Feb 1997 v123 n1
p55(7).

Watershed-specific model for streamflow, sediment, and metal transport. Helena M.

Solo-Gabriele, Frank E. Perkins. Journal of Environmental Engineering Jan 1997 v123 n1 p61(10)

1996

Cost-effectiveness of conservation and nutrient management practices in Pennsylvania. D.J. Epp, J.M. Hamlett. Journal of Soil and Water Conservation Nov-Dec 1996 v51 n6 p486(9).

The relationship between phosphorus and suspended sediment loads in Ontario watersheds. G.J. Wall, A.W. Bos, A.H. Marshall. Journal of Soil and Water Conservation Nov-Dec 1996 v51 n6 p504(4).

Systematic evaluation of pollutant removal by urban wet detention ponds. Jy S. Wu, Robert E. Holman, John R. Dorney. Journal of Environmental Engineering Nov 1996 v122 n11 p983(6).

Velocity and concentration profiles in sheet-flow layer of movable bed. B.M. Sumer, A. Kozakiewicz, J. Fredsoe, R. Deigaard. Journal of Hydraulic Engineering Oct 1996 v122 n10 p549(10).

Modeling sediment in gravel-bedded streams using HEC-6. Robert N. Havis, Carlos V. Alonso, John G. King. Journal of Hydraulic Engineering Oct 1996 v122 n10 p559(6).

A GIS procedure for automatically calculating the USLE LS factor on topographically complex landscape units. P.J.J. Desmet, G. Govers. Journal of Soil and Water Conservation Sep-Oct 1996 v51 n5 p427(7).

Designing instream flows to satisfy fish and human water needs. Hal Cardwell, Henriette I. Jager, Michael J. Sale. Journal of Water Resources Planning and Management Sep-Oct 1996 v122 n5 p356(8).

Using soil erosion models for global change studies. (Special Issue: Global Change & Terrestrial Ecosystems)(Editorial) A. Nearing, J. Williams, E. Skidmore, C. Valentin, K. King, R. Savabi. Journal of Soil and Water Conservation Sep-Oct 1996 v51 n5 p381(5).

The GCTE validation of soil erosion models for global change. (Global Climate and Terrestrial Ecosystems Core Project)(Special Issue: Global Change & Terrestrial Ecosystems) David T. Favis-Mortlock, John N. Quinton, W. Trevor Dickinson. Journal of Soil and Water Conservation Sep-Oct 1996 v51 n5 p397(7).

Scaling up processes and models from the field plot to the watershed and regional areas.

Mark (Special Issue: Global Change & Terrestrial Ecosystems) M.J. Kirkby, A.C. Imeson, G. Bergkamp, L.H. Cammeraat. *Journal of Soil and Water Conservation* Sep-Oct 1996 v51 n5 p391(6).

Nonpoint source pollution tests watershed approach. (Watershed Management: Clean Water's Next Act) R. Thomas Van Arsdall, Lawrence E. Selzer. *ENR* Sep 23, 1996 v237 n13 pW40(3).

10 issues in urban stormwater pollution control. Les Lange, Howard Andrews, Kirk Kisinger. *American City & County* Sep 1996 v111 n10 p36(8). City preaches, practices stormwater management. (Chattanooga, Tennessee) Tom Scott. *American City & County* Sep 1996 v111 n10 p42(1).

Modeling contaminated sediments. Robert K. Simons, Daryl B. Simons. *Civil Engineering* Sep 1996 v66 n9 p73(3).

National "environmental indicators" issued by EPA to track health of U.S. waters. Janet Pelley. *Environmental Science & Technology* Sep 1996 v30 n9 p381 A(1).

Development and testing of riverbank-stability analysis. Stephen E. Darby, Colin R. Thorne. *Journal of Hydraulic Engineering* August 1996 v122 n8 p443(12).

Fuzzy rule-based modeling of reservoir operation. Bijaya P. Shrestha, Lucien Duckstein, Eugene Z. Stakhiv. *Journal of Water Resources Planning and Management* July-August 1996 v122 n4 p262(8).

Numerical modeling for sediment-pass-through reservoirs. Howard H. Chang, Larry L. Harrison, Wing Lee, Scott Tu. *Journal of Hydraulic Engineering* July 1996 v122 n7 p381(8).

Modeling natural hydrodynamic systems with a differential-turbulence column. Brett Brunk, Monroe Weber-Shirk, Anna Jensen, Gerhard Jirka, Leonard W. Lion. *Journal of Hydraulic Engineering* July 1996 v122 n7 p373(8).

The potential of field turbidity measurements for the computation of total phosphorus and suspended solids loads. R.B. Grayson, B.L. Finlayson, C.J. Gippel, B.T. Hart. *Journal of Environmental Management* July 1996 v47 n3 p257(11).

ANSWERS-2000: runoff and sediment transport model. Faycal Bouraoui, Theo A. Dillaha. *Journal of Environmental Engineering* June 1996 v122 n6 p493 (10).

Settling velocities of fractal aggregates. Clifford P. Johnson, Xiaoyan Li, Bruce E. Logan. *Environmental Science & Technology* June 1996 v30 n6 p1911(8).

Measurements of erosion of undisturbed bottom sediments with depth. Joe McNeil, Catherine Taylor, Wilbert Lick. *Journal of Hydraulic Engineering* June 1996 v122 n6 p316(9).

Screening-level approach for estimating contaminant export from tributaries. Mark Velleux, Joseph Gailani, Doug Endicott. *Journal of Environmental Engineering* June 1996 v122 n6 p503(12).

Erosion and stability of a mine soil. Tien H. Wu, Man T. Stadler, Chin-wah Low. *Journal of Geotechnical Engineering* June 1996 v122 n6 p445(9).

Measurements of erosion of undisturbed bottom sediments with depth. Joe McNeil, Catherine Taylor, Wilbert Lick. *Journal of Hydraulic Engineering* June 1996 v122 n6 p316(9).

The accuracy of manual runoff and sediment sampling from erosion plots. M.A. Zobisch, P. Klingspor, A.R. Oduor. *Journal of Soil and Water Conservation* May-June 1996 v51 n3 p231(3).

Interrill soil erosion and slope steepness factors. J.M. Bradford, G.R. Foster. *Soil Science Society of America Journal* May-June 1996 v60 n3 p909(7).

Vegetative filter strip effects on sediment concentration in cropland runoff. C.A. Robinson, M. Ghaffarzadeh, R.M. Cruse. *Journal of Soil and Water Conservation* May-June 1996 v51 n3 p227(4).

Field-scale parameters. (Anion Transport in a Piedmont Ultisol, part 1) D.E. Radcliffe, P.M. Tillotson, P.F. Hendrix, L.T. West, J.E. Box, E.W. Tollner. *Soil Science Society of America Journal* May-June 1996 v60 n3 p755(7).

Evaluation of the detachment-transport coupling concept in the WEPP rill erosion equation. (Water Erosion Prediction Project) Chi-hua Huang, Joe M. Bradford, John M. Laflen. *Soil Science Society of America Journal* May-June 1996 v60 n3 p734(6).

Local-scale parameters. (Anion Transport in a Piedmont Ultisol, part 2) S.M. Gupte, D.E. Radcliffe, D.H. Franklin, L.T. West, E.W. Tollner, P.F. Hendrix. *Soil Science Society of America Journal* May-June 1996 v60 n3 p762(9).

Error estimate in Einstein's suspended sediment load method. Nadim M. Aziz. *Journal of Hydraulic Engineering* May 1996 v122 n5 p282(4).

Mechanical characteristics. (Bed-Load Transport, part 1) Chunhong Hu, Yujia Hui. *Journal of Hydraulic Engineering* May 1996 v122 n5 p245(10).

Stochastic characteristics. (Bed-Load Transport, part 2) Chunhong Hu, Yujia Hui. *Journal of Hydraulic Engineering* May 1996 v122 n5 p255(7).

Modeling non-uniform-sediment fluvial process by characteristics method. (response to Keh-Chia Yeh, Shiang-Jang Li and Wen-Li Chen, *Journal of Hydraulic Engineering*, vol.121, February 1995)(includes comments) J.L. Rahuel. *Journal of Hydraulic Engineering* April 1996 v122 n4 p226(2).

A cross section of stream channel restoration. G. Mathias Kondolf. *Journal of Soil and Water Conservation* March-April 1996 v51 n2 p119(7).

Key sources of uncertainty in QUAL2E Model of Passaic River. Charles S. Melching, Chun G. Yoon. *Journal of Water Resources Planning and Management* March-April 1996 v122 n2 p105(9).

Comparison and evaluation of different riprap stability formulas using field performance. Mahrez Ben Belfadhel, Guy Lefebvre, Karol Rohan. *Journal of Waterway, Port, Coastal and Ocean Engineering* Jan-Feb 1996 v122 n1 p8(8).

Sediment and chemical load reduction by grass and riparian filters. R.B. Daniels, J.W. Gilliam. *Soil Science Society of America Journal* Jan-Feb 1996 v60 n1 p246(6).

Guidelines for establishing warm season grass hedges for erosion control. C.L. Dewald, J. Henry, S. Bruckerhoff, J. Ritchie, S. Dabney, D. Shepherd, J. Douglas, D. Wolf. *Journal of Soil and Water Conservation* Jan-Feb 1996 v51 n1 p16(5).

Chebyshev model for water-quality management. Andrews K. Takyi, Barbara J. Lence. *Journal of Water Resources Planning and Management* Jan-Feb 1996 v122 n1 p40(9).

Design of class-I sedimentation tanks. Prabhata K. Swamee, Aditya Tyagi. *Journal of Environmental Engineering* Jan 1996 v122 n1 p71(3).

1995

Meandering rivers keep themselves in check. (mathematical model to explain regulated meandering of rivers) Marcus Chown. *New Scientist* Dec 9, 1995 v148 n2007 p19(1).

Fine suspended sediment transport rates. Junke Guo, William L. Wood. *Journal of Hydraulic Engineering* Dec 1995 v121 n12 p919(4).

A multi-objective approach to integrating agricultural economic and environmental policies. P.O. Lakshiminarayan, S.R. Johnson, A. Bouzaher. *Journal of Environmental Management* Dec 1995 v45 n4 p365(14).

Simple equations to express settling column data. Charles R. Ott. *Journal of Environmental Engineering* Dec 1995 v121 n12 p933(2).

Decision making process in a nonpoint pollution control model. Dragan Miljkovic. *Journal of Environmental Management* Nov 1995 v45 n3 p255(8).

Long-term simulation of fine-grained sediment transport in large reservoir. C. Kirk Ziegler, Bradley S. Nisbet. *Journal of Hydraulic Engineering* Nov 1995 v121 n11 p773(9).

Parametric modeling and estimation of acoustic sediment properties using a system identification approach. Zobeida Cisneros, Luc Peirlinckx, Leo Pierre Van Biesen. *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control* Nov 1995 v42 n6 p1002(7).

Optimal control approach for sedimentation control in alluvial rivers. Carlos C. Carriaga, Larry W. Mays. *Journal of Water Resources Planning and Management* Nov-Dec 1995 v121 n6 p408(10).

The political economy of dredging to offset sediment impacts on water quality in Ohio's state park lakes. (Special Wetlands Issue) Timothy S. Lehman, Fred J. Hitzhusen, Marvin Batte. *Journal of Soil and Water Conservation* Nov-Dec 1995 v50 n6 p659(4).

Sediment-laden flow in open channels from two-phase flow viewpoint. Zhixian Cao, Liangyan Wei, Jianheng Xie. *Journal of Hydraulic Engineering* Oct 1995 v121 n10 p725(11).

A sediment transport capacity formulation for application to large channel networks. (Special Issue: Water Research and Management in Semiarid Environments) Jurgen Garbrecht, Roger Kuhnle, Carlos Alonso. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p527(3).

The IxEa erosivity index: an index with the capacity to give more direct consideration to hydrology in predicting short-term erosion in the USLE modeling environment. (Universal Soil Erosion Equation)(Special Issue: Water Research and Management in Semiarid Environments) P.I.A. Kinnell. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p507(6).

The applicability of RUSLE to geomorphic studies. (Revised Universal Soil Loss Equation) (Special Issue: Water Research and Management in Semiarid Environments) T.J. Toy, W.R. Osterkamp. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p498(6).

Effects of aggregation on soil erodibility: Australian experience. (Special Issue: Water Research and Management in Semiarid Environments) R.J. Loch, C. Pocknee. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p504(3).

Assessing uncertainties in WEPP's soil erosion predictions on rangelands. (Water Erosion Prediction Project)(Special Issue: Water Research and Management in Semiarid Environments) M. Tiscareno-Lopez, M.A. Weltz, V.L. Lopes. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p512(5).

Dynamic, distributed simulation of watershed erosion: the KINEROS2 and EUROSEM models. (Special Issue: Water Research and Management in Semiarid Environments) R.E. Smith, D.C. Goodrich, J.N. Quinton. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p517(4).

Application of WEPP and GIS- GRASS to a small watershed in Indiana. (Water Erosion Prediction Project; Geographic Information System-Geographical Resource Analysis Support System)(Special Issue: Water Research and Management in Semiarid Environments) M.R. Savabi, D.C. Flanagan, B. Hebel, B.A. Engel. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p477(7).

The future of RUSLE: inside the new Revised Universal Soil Loss Equation. (Special Issue: Water Research and Management in Semiarid Environments) Daniel Yoder, Joel Lown. *Journal of Soil and Water Conservation* Sept-Oct 1995 v50 n5 p484(6).

Sediment transport under sheet-flow conditions. Toshiyuki Asano. *Journal of Waterway, Port, Coastal and Ocean Engineering* Sept-Oct 1995 v121 n5 p239(8).

Newest soil erosion formula "goes commercial." Dennis Senft, Hank Becker. *Agricultural Research* Sept 1995 v43 n9 p11(1).

Particle size and velocity discrimination in a sediment-laden turbulent flow using phase Doppler anemometry. S.J. Bennett, J.L. Best. *Journal of Fluids Engineering* Sept 1995 v117 n3 p505(7).

STEEP solutions to soil erosion. (Solutions to Environmental and Economic Problems) Kathryn Barry Stelljes. *Agricultural Research* August 1995 v43 n8 p8(5).

Effects of sediment on drainage-culvert serviceability. Vassilios A. Tsihrintzis. *Journal of Performance of Constructed Facilities* August 1995 v9 n3 p172(12).

Bed topography and sediment sorting in channel bend with unsteady flow. Chin-lien Yen, Kwan Tun Lee. *Journal of Hydraulic Engineering* August 1995 v121 n8 p591(9).

An integrated approach for prioritisation of watersheds. (India) J. Adinarayan, N. Rama Krishna, K. Gopal Rao. *Journal of Environmental Management* August 1995 v44 n4 p375(10).

Soil and fecal coliform trapping by grass filter strips during simulated rain. M.S. Coyne, R.A. Gilfillen, R.W. Rhodes, R.L. Blevins. *Journal of Soil and Water Conservation* July-August 1995 v50 n4 p405(4).

Empirical analysis of slope and runoff for sediment delivery from interrill areas. Chi-hua Huang. *Soil Science Society of America Journal* July-August 1995 v59 n4 p982(9).

In-situ depth profiling of particle sizes. P. Gentien, M. Lunven, M. Lehaitre, J.L. Duvent. *Deep-Sea Research. Part I, Oceanographic Research Papers* August 1995 v42 n8 p1297(15).

Soil erosion estimates and costs. (includes reply)(Letter to the Editor) Pierre Crosson, David Pimentel, C. Harvey, P. Resosudarno, K. Sinclair, D. Kurz, M. McNair, S. Crist, L. Shpritz, L. Fitton, R. Saffouri, R. Blair. *Science* July 28, 1995 v269 n5223 p461(5).

Selection of gravel-transport formula for stream modeling. (response to Howard H. Chang, *Journal of Hydraulic Engineering*, vol. 120, May 1994) Jonathan B. Laronne, Ian Reid, Lev Meerovich, D. Mark Powell. *Journal of Hydraulic Engineering* July 1995 v121 n7 p567(2).

Statistical approach to bed-material surface sampling. Luigi Fraccarollo, Andrea Marion. *Journal of Hydraulic Engineering* July 1995 v121 n7 p540(6). Turbulent structure of water and clay suspensions with bed load. (response to Zhaoyin Wang and Peter Larsen, *Journal of Hydraulic Engineering*, vol.120, May 1994) Hubert Chanson. *Journal of Hydraulic Engineering* July 1995 v121 n7 p562(2).

Environmental analysis. (Application Reviews) Ray E. Clement, Gary A. Eiceman, Carolyn J. Koester. *Analytical Chemistry* June 15, 1995 v67 n12 p221(35).

Criteria for incipient motion of spherical sediment particles. Chi-Hai Ling. *Journal of Hydraulic Engineering* June 1995 v121 n6 p472(7).

Raindrop-induced soil detachment and sediment transport from Interrill areas. (Division S-1-Soil Physics) P.P. Sharma, S.C. Gupta, G.R. Foster. *Soil Science Society of America Journal* May-June 1995 v59 n3 p727(8).

Incipient motion of sand-gravel sediment mixtures. (response to Roger A. Kuhnle, *Journal of Hydraulic Engineering*, vol.119, December 1993) Roger Bettess. *Journal of Hydraulic Engineering* May 1995 v121 n5 p448(3).

Sediment yield from disturbed earth systems. S.A. Schumm, David K. Rea. *Geology* May 1995 v23 n5 p391(4).

Urban Stormwater Modeling and Simulation. (book reviews) Ben Chie Yen. *Bulletin of the American Meteorological Society* April 1995 v76 n4 p564(2).

Laboratory determination of interrill soil erodibility. C.C. Truman, J.M. Bradford. *Soil Science Society of America Journal* March-April 1995 v59 n2 p519(8).

Storm and entrainment effects on tributary sediment loads. R Gopakumar Deborah H. Lee. *Journal of Hydraulic Engineering* March 1995 v121 n3 p294(2).

Laboratory determination of interrill soil erodibility. C.C. Truman, J.M. Bradford. *Soil Science Society of America Journal* March-April 1995 v59 n2 p519(8).

Slope stabilization using old rubber tires and geotextiles. Paul S.H. Poh, Bengt B. Broms. *Journal of Performance of Constructed Facilities* Feb 1995 v9 n 1 p76(4).

Continuous-time water and sediment-routing model for large basins. J.G. Arnolds, J.R. Williams, D.R. Maidment. *Journal of Hydraulic Engineering* Feb 1995 v121 n2 p171(13).

Environmental and economic costs of soil erosion and conservation benefits. David Pimentel, C. Harvey, P. Resosudarmo, K. Sinclair, D. Kurz, M. McNair, S. Crist, L. Shpritz, I. Fitton, R. Saffouri, R. Blair. *Science* Feb 24, 1995 v267 n5201 p1117(7).

Turbulence: Perspectives on Flow and Sediment Transport. (book reviews) Bernard O. Bauer. *The Geographical Review* Jan 1995 v85 n1 p113(3).

1994

Operational urban models: state of the art. Michael Wegener. *Journal of the American Planning Association* Wntr 1994 v60 n1 p17(13).

Retrospective on large-scale urban models. Douglass B. Lee. *Journal of the American Planning Association* Wntr 1994 v60 n1 p35(6).

Prediction of sediment yield. (Technical Notes) U.C. Kothyari, A.K. Tiwari, Ranvir Singh. *Journal of Irrigation and Drainage Engineering* Nov-Dec 1994 v120 n6 p1122(10).

Economic impacts of erosion management measures in coastal drainage basins. Ching-Cheng Chang, Jay D. Atwood, Klaus Alt, Bruce A. McCarl. *Journal of Soil and Water Conservation* Nov-Dec 1994 v49 n6 p606(6).

Quantification of soil loss from eroded soil phases. K.R. Olson, R. Lal, L.D. Norton, T.E. Fenton. *Journal of Soil and Water Conservation* Nov-Dec 1994 v49 n6 p591(6).

Regression models for estimating soil properties by landscape position. S.C. Brubaker, A.J. Jones, K. Frank, D.T. Lewis. *Soil Science Society of America Journal* Nov-Dec 1994 v58 n6 p1763(5).

Sediment deposition and entrapment in vegetated streambeds. Steven R. Abt, Warren P. Clary, Christopher I. Thornton. *Journal of Irrigation and Drainage Engineering* Nov-Dec 1994 v120 n6 p1098(14).

Depositional turbidity currents laden with poorly sorted sediment. Marcelo H. Garcia. *Journal of Hydraulic Engineering* Nov 1994 v120 n11 p1240(24).

Predicting sediment yield in storm-water runoff from urban areas. Thomas W. Haster, Wesley P. James. *Journal of Water Resources Planning and Management* Sept-Oct 1994 v120 n5 p630(21).

Nonpoint-pollution model sensitivity to grid-cell size. J. Garbrecht. *Journal of Water Resources Planning and Management* Sept-Oct 1994 v120 n5 p738(5).

A cellular model of braided rivers. A. Brad Murray, Chris Paola. *Nature* Sept 1, 1994 v371 n6492 p54(4).

Data analysis of bed concentration of suspended sediment. Julio A. Zyserman, Jorgen Fredsoe. *Journal of Hydraulic Engineering* Sept 1994 v120 n9 p1021(22).

Sediment concentration below free overfall. O.R. Stein, P.Y. Julien. *Journal of Hydraulic Engineering* Sept 1994 v120 n9 p1043(17).

Conservative characteristics-based schemes for mass transport. C.W. Li, T.S. Yu. *Journal of Hydraulic Engineering* Sept 1994 v120 n9 p1089(11).

Turbulence: Perspectives on Flow and Sediment Transport. (book reviews) Michael Church. *The Professional Geographer* August 1994 v46 n3 p389(2).

New particle-labeling technique for use in biological and physical sediment transport studies. Ilhan Olmez, Francis Pink, Robert A. Wheatcroft. *Environmental Science & Technology* August 1994 v28 n8 p1487(4).

Streambed armoring. C.O. Chin, B.W. Melville, A.J. Raudkivi. *Journal of Hydraulic Engineering* August 1994 v120 n8 p899(20).

Software utilizing Imhoff cone volumes to estimate furrow-irrigation erosion. R.E. Sojka, R.D. Lentz, J.A. Foerster. *Journal of Soil and Water Conservation* July-August 1994 v49 n4 p400(7).

Simulation. (Water-Treatment - System Design for Turbidity Removal, part 1) H.B. Dharmappa, S. Vigneswaran, J. Verink, O. Fujiwara. *Journal of Environmental Engineering* July-August 1994 v120 n4 p900(21).

Hydraulic flow and water quality characteristics in rill erosion. I. Shainberg, J.M. Laflen, J.M. Bradford, L.D. Norton. *Soil Science Society of America Journal* July-August 1994 v58 n4 p1007(6).

Relative importance of mechanisms determining decomposition of a southeastern black water stream. Russell B. Rader, J.V. McArthur, John M. Aho. *The American Midland Naturalist* July 1994 v132 n1 p19(13).

Cleaning up urban stormwater: the storm drain stenciling approach (or getting to the nonpoint source). John Coburn. *Journal of Soil and Water Conservation* July-August 1994 v49 n4 p312(4).

Hydraulic flow and water quality characteristics in nil erosion. I. Shainberg, J.M. Laflen, J.M. Bradford, L.D. Norton. *Soil Science Society of America Journal* July-August 1994 v58 n4 p1007(6).

Streambed erosion: measuring sediment's ebb and flow. Hank Becker. *Agricultural Research* July 1994 v42 n7 p10(2).

Erosion, Transport, and Deposition Processes: Theories and Models. (book reviews) *The Canadian Geographer* Summer 1994 v38 n2 p189(1).

Slope readjustment: a new model for the development of submarine fans and aprons. W.C. Ross, B.A. Halliwell, J.A. May, D.E. Watts, J.P.M. Syvitski. *Geology* June 1994 v22 n6 p511(4).

Computation of transverse mixing in streams. Alexander C. Demetracopoulos. *Journal of Environmental Engineering* May-June 1994 v120 n3 p699(8).

RUSLE revisited: status, questions, answers, and the future. (Revised Universal Soil Loss Equation) K.G. Renard, G.R. Foster, D.C. Yoder, D.K. McCool. *Journal of Soil and Water Conservation* May-June 1994 v49 n3 p213(8).

Sediment and debris removal inlet structure for canal pipelines. Gilbert Horrocks, H. Lee Wimmer, Pam McMullin. *Journal of Irrigation and Drainage Engineering* May-June 1994 v120 n3 p607(10).

Simple equations to express settling column data. Adem Ozer. *Journal of Environmental Engineering* May-June 1994 v120 n3 p677(6).

In situ estimation of transport parameters: a field demonstration. William R. Wise, Randall J. Charbeneau. *Ground Water* May-June 1994 v32 n3 p420(11).

Modeling of infiltration from trenches for storm-water control. Michael Duchene, Edward A. McBean, Neil R. Thomson. *Journal of Water Resources Planning and Management* May-June 1994 v120 n3 p276(18).

Selection of gravel-transport formula for stream modeling. Howard H. Chang. *Journal of Hydraulic Engineering* May 1994 v120 n5 p646(6).

Monitoring the effects of urban runoff on recreational waters. Richard Kebabjian. *Journal of Environmental Health* May 1994 v56 n9 p15(4).

Fine-grained sediment transport in Pawtuxet River, Rhode Island. C. Kirk Ziegler, Bradley Nisbet. *Journal of Hydraulic Engineering* May 1994 v120 n5 p561(16).

Instantaneous-unit sediment graph. N.S. Raghuwanshi, R.A. Rastogi, Santosh Kumar. *Journal of Hydraulic Engineering* April 1994 v120 n4 p495(9).

Statistical techniques for assessing water-quality effects of BMPs. (best management practices) John F. Walker. *Journal of Irrigation and Drainage Engineering* March-April 1994 v120 n2 p334(14).

Comment on "Length-slope factors for the Revised Universal Soil Loss Equation: simplified method of estimation." (includes reply) George R. Foster, D.K. McCool. *Journal of Soil and Water Conservation* March-April 1994 v49 n2 p171(11).

Soil conservation planning at the watershed level using the Universal Soil Loss Equation with GIS and microcomputer technologies: a case study. (geographic information systems) K.T. Mellerowicz, H.W. Rees, T.L. Chow, I. Ghanem. *Journal of Soil and Water Conservation* March-April 1994 v49 n2 p194(7).

Does reentrainment occur during cohesive sediment settling? Y.L. Lau, B.G. Krishnappan. *Journal of Hydraulic Engineering* Feb 1994 v120 n2 p236(9).

Runoff detention for flood volume or erosion control. A. Osman Akan, Edward N. Antoun. *Journal of Irrigation and Drainage Engineering* Jan-Feb 1994 v120 n1 p168(11).

Storm and entrainment effects on tributary sediment loads. Deborah H. Lee, Keith W. Bedford, Chieh-Cheng Yen. *Journal of Hydraulic Engineering* Jan 1994 v120 n1 p81(23).

Effective sediment-transporting discharge from magnitude-frequency analysis. David B. Nash. *Journal of Geology* Jan 1994 v102 n1 p79(17).

1993

Model for urban river cleanup. Sandy Cleva. *Geotimes* Dec 1993 v38 n12 p6(2).

Effect of bank stability on geometry of gravel rivers. Robert G. Millar, Michael C. Quick. *Journal of Hydraulic Engineering* Dec 1993 v119 n12 p1343(21).

Incipient motion of sand-gravel sediment mixtures. Roger A. Kuhrle. *Journal of Hydraulic Engineering* Dec 1993 v119 n12 p1400(16).

Three-dimensional eutrophication model of Chesapeake Bay. Carl F. Cerco, Thomas Cole. *Journal of Environmental Engineering* Nov-Dec 1993 v119 n6 p1006(20).

Erosion reaches crisis proportions; soil conservation can no longer be postponed. Edwin B. Lake, Aly M. Shady. *Agricultural Engineering* Nov 1993 p8(6).

Stochastic theory for irregular stream modeling. (response to Shu-Guang Li, Lakshmi Venkataraman and Dennis McLaughlin, *Journal of Hydraulic Engineering*, vol. 118, p. 1840, August 1992) Jian-Jun Zhou. *Journal of Hydraulic Engineering* Nov 1993 v119 n11 p1310(4).

Runoff as a resource. (storm-water-management strategy) Jamil F. Bou-Saab. *Civil Engineering* Oct 1993 v63 n10 p70(2).

Nonpoint source pollution impacts of alternative agricultural management practices in Illinois: a simulation study. Donald L. Phillips, Paul D. Hardin, Verel W. Benson, Joseph V. Baglio. *Journal of Soil and Water Conservation* Sept-Oct 1993 v48 n5 p449(9).

Analyses of slope and runoff factors based on the WEPP erosion model. Chi-hua Huang, Joe M. Bradford. *Soil Science Society of America Journal* Sept-Oct 1993 v57 n5 p1176(8).

Modeling subsurface drainage and surface runoff with WEPP. (water erosion prediction project) M.R. Savabi. *Journal of Irrigation and Drainage Engineering* Sept-Oct 1993 v119 n5 p801(13).

A simple method of correction for forward Rayleigh scattering in turbidity measurements. Steven Siano. *Applied Optics* August 20, 1993 v32 n24 p4646(6).

Marginal cost effectiveness analysis for agricultural nonpoint source water quality control. D.J. Walker, B.L. Calkins, J.R. Hamilton. *Journal of Soil and Water Conservation* July-August 1993 v48 n4 p368(5).

On particle-size distributions in soils. Q. Wu, M. Borkovec, H. Sticher. *Soil Science Society of America Journal* July-August 1993 v57 n4 p883(8).

Improved models of particle-size distribution: an illustration of model comparison techniques. G.D. Buchan, K.S. Grewal, A.B. Robson. *Soil Science Society of America Journal* July-August 1993 v57 n4 p901(8).

Type II sedimentation: removal efficiency from column-settling tests. P. Udaya Bhaskar, Sanjeev Chaudhari, Mohammad Jawed, H. Ali San, H.Z. Sarikaya, Ravindra M. Srivastava. *Journal of Environmental Engineering* July-August 1993 v119 n4 p757(4).

Towards modeling support system for simulation of water quality. Piotr Jankowski, Craig ZumBrunnen. *Journal of Computing in Civil Engineering* July 1993 v7 n3 p354(18).

Particle size analysis. Howard G. Barth, Shao-Tang Sun. *Analytical Chemistry* June 15, 1993 v65 n12 p55R(12).

Predicting soil detachment by raindrops. P.P. Sharma, S.C. Gupta, G.R. Foster. *Soil Science Society of America Journal* May-June 1993 v57 n3 p674(7).

Basin-scale modeling as tool for water-resource planning. A. Bryce Cooper, Adelbert B. Bottcher. *Journal of Water Resources Planning and Management* May-June 1993 v119 n3 p306(18).

Error assessment in the Universal Soil Loss Equation. L.M. Risse, M.A. Nearing, A.D. Nicks, J.M. Laflen. *Soil Science Society of America Journal* May-June 1993 v57 n3 p825(9).

Critical shear stress of natural sediments. Peter R. Wilcock. *Journal of Hydraulic Engineering* April 1993 v119 n4 p491(15).

Geographic information systems in urban storm-water management. Steffen P. Meyer, Tarek H. Salem, John W. Labadie. *Journal of Water Resources Planning and Management* March-April 1993 v119 n2 p206(23).

Experimental study of processes and particle-size distributions of eroded soil. Deanna Durnford, J. Phillip King. *Journal of Irrigation and Drainage Engineering* March-April 1993 v119 n2 p383(16).

Evaluation of runoff and erosion models. Tein H Wu, James A. Hall, James V Bonta. *Journal of Irrigation and Drainage Engineering* March-April 1993 v119 n2 p364(19).

Scavenging of small particles by fast-sinking porous aggregates. Keith D. Stolzenbach. *Deep-Sea Research. Part I, Oceanographic Research Papers* Feb 1993 v40 n2 p359(11).

Miracle grass as erosion-control hedge. (National Research Council reports vetiver grass effective in controlling erosion in tropical countries) (Brief Article) *Science News* Feb 6, 1993 v143 n6 p95(1).

A device to collect sediment cores: and an experiment for their chemical analysis. (studying chemistry) R. Del Delumyea, Donna L. McCleary. *Journal of Chemical Education* Feb 1993 v70 n2 p172(2).

Riprap criteria below pipe outlet. Mahmood Shafai-Bajestan, Maurice L. Albertson. *Journal of Hydraulic Engineering* Jan-Feb 1993 v119 n2 p181(20).

Comparison of physical transport processes in noncohesive river sediments. D.D. Reible, S.A. Savant-Malhiet. *Journal of Environmental Engineering* Jan-Feb 1993 v119 n1 p90(13).

Organisms and sediments: relationships and applications. R. Goldring, J.E. Pollard. *Journal of the Geological Society* Jan 1993 v150 n1 p137(3).

1992

Downstream fining by selective deposition in a laboratory flume. Chris Paola, Gary Parker, Rebecca Seal, Sanjiv K. Sinha, John B. Southard, Peter R. Wilcock. *Science* Dec 11, 1992 v258 n5089 p1757(4).

New total sediment-load sampler. Leo C. Van Rijn, Moustafa T.K. Gaweesh. *Journal of Hydraulic Engineering* Dec 1992 v118 n12 p1686(6).

A mesh-bag method for field assessment of soil erosion. Yuch-Ping Hsieh. *Journal of Soil and Water Conservation* Nov-Dec 1992 v47 n6 p495(4).

Land use and management effects on nonpoint loading from miamian soil. M.L. Thomas, R. Lal, T. Logan, N.R. Fausey. Soil Science Society of America Journal Nov-Dec 1992 v56 n6 p1871(5).

A comparison of aggregate profiles with sediment trap fluxes. I.D. Walsh, W.D. Gardner. Deep Sea Research (Part A) Nov-Dec 1992 v39 n11-12A p1817(18).

Drag coefficient and fall velocity of nonspherical particles. Ramon Fuentes, Mary L. Alonso, Julian Aguirre-Pe. Journal of Hydraulic Engineering Nov 1992 v118 n11 p1589(4).

Vertical sediment distribution. (comment on Jin Ren Ni and Guang Qian Wang, Journal of Hydraulic Engineering, vol.117, September 1991; includes reply) Vito Ferro. Journal of Hydraulic Engineering Oct1992 v118 n10 p1458(4).

Mean size distribution of bed load on Goodwin Creek. Roger A. Kuhnle, Joe C. Willis. Journal of Hydraulic Engineering Oct 1992 v118 n10 p1443(4).

Length-slope factors for the Revised Universal Soil Loss Equation: simplified method of estimation. Ian D. Moore, John P. Wilson. Journal of Soil and Water Conservation Sept-Oct 1992 v47 n5 p423(6).

Predicting sediment loads. (Special Issue: Environmental) Krishan P. Singh, Ali Durgunoglu. Civil Engineering Oct 1992 v62 n10 p64(2).

Modeling of rectangular settling tanks. Siping Zhou, John A. McCorquodale. Journal of Hydraulic Engineering Oct 1992 v118 n10 p1391(15).

Calibrating SHE soil-erosion model for different land coers. (Systeme Hydrologique European) J.M. Wicks, J.C. Bathurst. Journal of Irrigation and Drainage Engineering Sept-Oct 1992 v118 n5 p708(16).

Conceptual bed-load transport model and verification for sediment mixtures. Shaohua Marko Hsu, Forrest M. Holly Jr. Journal of Hydraulic Engineering August 1992 v118 n8 p1135(18).

Concentrating suspended sediment samples by filtration: effect on primary grain-size distribution. Ian G. Droppo, Bommanna G. Krishnappan, Edwin D. Ongley. Environmental Science & Technology August 1992 v26 n8 p1655(4).

Hedging against erosion. Doral Kemper, Seth Dabney, Larry Kramer, Darrel Dominick, Tom Keep. Journal of Soil and Water Conservation July-August 1992 v47 n4 p284(5).

Estimating the water-dispersible clay content of soils. (Division S-5 - Soil Genesis, Morphology Mark & Classification) S.C. Brubaker, C.S. Holzhey, B.R. Brasher. Soil Science Society of America Journal July-August 1992 v56 n4 p1226(7).

Computerized calculations for conservation planning. Kenneth G. Renard. Agricultural Engineering July 1992 p16(2).

A view on needs. (the use of erosion equations in farm management) Richard Johnson. Agricultural Engineering July 1992 p22(1).

A powerful tool. (use of the Water Erosion Prediction Project in US farms) J.M. Laflen, D.C. Flanagan. Agricultural Engineering July 1992 p18(2).

Properties of various sediment sampling procedures. Panayiotis Diplas, Jon B. Fripp. Journal of Hydraulic Engineering July 1992 v118 n7 p955(16).

Turbulence characteristics of sediment-laden flows in open channels. D.A. Lyn. Journal of Hydraulic Engineering July 1992 v118 n7 p971(18).

Manual for the geochemical analyses of marine sediments and suspended particulate matter. Douglas H. Loring, Reijo T.T. Rantala. Earth-Science Reviews July 1992 v32 n4 p235(49).

Vertical distribution of suspended sediment in uniform open-channel flow. Motohiko Umeyama. Journal of Hydraulic Engineering June 1992 v118 n6 p936(6).

Measuring physical characteristics of particles: a new method of simultaneous measurement for size, settling velocity and density of constituent matter. Kumiko Azetsu-Scott, Bruce D. Johnson. Deep Sea Research (Part A) June 1992 v39 n6A p1057(10).

Entrainment of bed sediment into suspension. (response to Marcelo Garcia and Gary Parker, Journal of Hydraulic Engineering, vol.117, April 1991) Ismail Celik, Wolfgang Rodi. Journal of Hydraulic Engineering June 1992 v118 n6 p946(3).

Vertical distribution of suspended sediment in uniform open-channel flow. Motohiko Umeyama. Journal of Hydraulic Engineering June 1992 v118 n6 p936(6).

Bed-load and suspended-load transport of nonuniform sediments. (response to Prabhata K. Swamee and Chandra Shekhar P. Ojha, Journal of Hydraulic Engineering, vol.117, June 1991) R. Srivastava, D.N. Contractor. Journal of Hydraulic Engineering June 1992 v118 n6 p948(3).

Storm runoff detention for pollutant removal. (Technical Papers) A. Osman Akan. Journal of Environmental Engineering May-June 1992 v118 n3 p380(10).

Imhoff cone determination of sediment in irrigation runoff. (Division S-6 - Soil & Water Management & Conservation) R.E. Sojka, D.L. Carter, M.J. Brown. Soil Science Society of America Journal May-June 1992 v56 n3 p884(7).

Type II sedimentation: removal efficiency from column-settling tests. (Technical Notes) Ravindra M. Srivastava. Journal of Environmental Engineering May-June 1992 v118 n3 p438(4).

Using expert systems and process models to enhance U.S. agriculture. V.W. Benson, B.L. Harris, C.W. Richardson, C.A. Jones, J.R. Williams. Journal of Soil and Water Conservation May-June 1992 v47 n3 p234(2).

Impact of flow variability on error in estimation of tributary mass loads. (Technical Papers) Stephen D. Preston, Victor J. Bierman Jr., Stephen E. Silliman. Journal of Environmental Engineering May-June 1992 v118 n3 p402(18).

Menu of coupled velocity and sediment-discharge relations for rivers. (comment on M. Fazle Karim and John F. Kennedy, Journal of Hydraulic Engineering, vol.116, August 1990) Scott M. Taylor, M. Gamal Mostafa. Journal of Hydraulic Engineering May 1992 v118 n5 p812(3).

Distant look at pollution. (remote pollution sensing devices compared to standard point-samplers) (News) Civil Engineering May 1992 v62 n5 p13(2).

Sediment and aquatic habitat in river systems. (relationship between sediment transport and river ecology) Journal of Hydraulic Engineering May 1992 v118 n5 p669(19).

Cohesionless, fine-sediment bed forms in shallow flows. Peter A. Mantz. Journal of Hydraulic Engineering May 1992 v118 n5 p743(22).

Suspended sediment-transport capacity for open channel flow. (comment on Ismail Celik and Wolfgang Rodi, Journal of Hydraulic Engineering, vol. 117, February 1991) Rasmus Wiuff Journal of Hydraulic Engineering May 1992 v118 n5 p823(5).

Mechanics of saltating grains. (part 2) Masato Sekine, Hideo Kikkawa. Journal of Hydraulic Engineering April 1992 v118 n4 p536(23).

Bed-load transport on tranverse slope. (part 1) Masato Sekine, Gary Parker. Journal of Hydraulic Engineering April 1992 v118 n4 p513(23).

Reservoir desiltation and long-term storage capacity. (Reservoir Sedimentation, part 2) Jiahua Fan, Gregory L. Morris. *Journal of Hydraulic Engineering* March 1992 v118 n3 p370(15).

Velocity distribution in uniform sediment-laden flow. (includes appendices) Motohiko Umeyama, Franciscus Gerritsen. *Journal of Hydraulic Engineering* Feb 1992 v118 n2 p229(17).

Routing of heterogeneous sediments over movable bed: model development. (includes appendices) Andre Van Niekerk, Koen R. Vogel, Rudy L. Slingerland, John S. Bridge. *Journal of Hydraulic Engineering* Feb 1992 v118 n2 p246(17).

Routing of heterogeneous sediments over movable bed: model verification. (includes appendices) Koen R. Vogel, Andre Van Niekerk, Rudy L. Slingerland, John S. Bridge. *Journal of Hydraulic Engineering* Feb 1992 v118 n2 p263(17).

Nitrogen fertilizer and dairy manure effects on corn yield and soil nitrate. (Soil Fertility & Plant Nutrition) William F. Jokela. *Soil Science Society of America Journal* Jan-Feb 1992 v56 n1 p148(7).

Size characteristics of sediment from agricultural soils. L.D. Meyer, W.C. Harmon. *Journal of Soil and Water Conservation* Jan-Feb 1992 v47 n1 p107(5).

1991

Upland and coastal sediment sources in a Chesapeake Bay estuary. W. Andrew Marcus, Michael S. Kearney. *The Annals of the Association of American Geographers* Sept 1991 v81 n3 p408(17).

Bedload transport. (sampling riverbeds) Bill Gomez. *Earth-Science Reviews* August 1991 v31 n2 p89(44).

Relation between sediment yield and gradient on debris-covered hillslopes, Walnut Gulch, Arizona. Athol D. Abrahams, Anthony J. Parsons. *The Geological Society of America Bulletin* August 1991 v103 n8 p1109(5).

Individual particle analysis of suspended materials in Onondaga Lake, New York. David L. Johnson, Jianfli Jiao, Saul G. DosSantos, Steven W. Effler. *Environmental Science & Technology* April 1991 v25 n4 p736(9).

River rivalry. (Georgia, Florida and Alabama fight over water rights of the Chattahoochee river) (American Survey) *The Economist* March 30, 1991 v318 n7700 pA26(2).

1990

Suspended clay and the population dynamics of planktonic rotifers and cladocerans. Kevin L. Kirk, John J. Gilbert. *Ecology* Oct 1990 v71 n5 p1741(15).

An evaluation of transfer - function/noise models of suspended sediment concentration. Karen A. Lemke. *The Professional Geographer* August 1990 v42 n3 p324(13).

Resource enhancement by indirect effects of grazers: armored catfish, algae, and sediment. Mary E. Power. *Ecology* June 1990 v71 n3 p897(8).

1989

Where erosion and development meet. (Around the U.S.) David W. Owens. *EPA Journal* Sept-Oct 1989 v15 n5 p44(2).

Soils in the urban jungle. (soil composition research) E.M. Bridges. *Geographical Magazine* Sept 1989 v61 n9 p51(3).

Lag-time routing of suspended sediment concentrations during unsteady flow. W. Andrew Marcus. *The Geological Society of America Bulletin* May 1989 v101 n5 p644(16).

1986

Consideration of offsite impacts in targeting soil conservation programs. Marc O. Ribaud. *Land Economics* Nov 1986 v62 n4 p402(10).

The effect of technical progress on erosion damage and economic incentives for soil conservation. David J. Walker, Douglas L. Young. *Land Economics* Feb 1986 v62 n1 p83(11).

1985

The trouble with tracking turbidity. (filtering bacteria from drinking water) Ivars Peterson. *Science News* July 6, 1985 v128 p4(1).

1982

Stop soil erosion with 'soft flow screens.' Dick Yost. *Mother Earth News* July-Aug 1982 p52(1).

MATRIX I - HYDROLOGY, SEDIMENTOLOGY, SIZE DISTRIBUTION

<i>ACRONYM</i>	<i>NAME</i>	<i>HYDR</i>	<i>SED YIELD</i>	<i>SED SIZE</i>	<i>SOURCE</i>
AGNPS	Agricultural Non-Point Source Pollution Model	Y	Y	Y	1
ANSWERS	Aerial Non-Point Source Watershed Environmental Response Simulation	Y	Y	Y	2
Auto-QI	Automated Q-IIL Urban Drainage Area Simulator	Y	Y	?	3
BASIN	Basin Scale Nutrient Delivery Model	Y	N	N	4
CREAMS/GLEAMS	Chemicals and Runoff in Agricultural Management Systems	Y	Y	Y	5
DR3M	Distributed Routing Rainfall Runoff Model	Y	N	N	6
DR3M-QUAL	Distributed Routing Rainfall Runoff Model-Quality	Y	?	?	7
FESHM	Finite Element Sediment Hydrology Model	Y	Y	Y	8
FESWMS-2DH	Finite Element Surface Water Modeling System - 2D Horizontal Hydraulics	Y	N	N	9
FHWA	Federal Highway Administration Model	Y	N	N	10
GWLF	Generalized Watershed Loading Functions	Y	Y	?	11
HEC1	Flood Hydrograph Model	Y	N	N	12
HEC5Q	Simulation of Flood Control & Conservation Systems	N	N	N	13
HSPF	Hydrological Simulation - FORTRAN	Y	Y	Y	14
NPSMAP	Nonpoint Source Model for Analysis and Planning	Y	N	N	15
P8-UCM	Urban Catchment Model	Y	N	N	16
QUAL2E	Enhanced Stream Water Quality Model	N	N	N	17
RUSLE	Revised Universal Soil Loss Equation	N	Y	N	18
SEDCAD+, V3	Civil Software Version of SEDIMOT II	Y	Y	Y	19
SEDIMOTII	Sedimentology by Distributed Modeling Techniques - Version II	Y	Y	Y	20
SEDIMOTIII	Sedimentology by Distributed Modeling Techniques - Version III	Y	Y	Y	21
SIMPLE (STORM)	Nonpoint Source Simulation Model	Y	Y	Y	22
SIMPTM	Simplified Particle Transport Model	Y	Y	Y	23
SLAMM	Source Loading and Management Model	Y	Y	?	24
SLOSS-PHOSH	Sediment and Phosphorus Prediction	N	Y	?	25
STORM	Storage, Treatment, Overflow, Runoff Model	Y	Y	?	26
SWMM	Stormwater Management Model	Y	Y	?	27
SWRRBWQ	Simulation for Water Resources in Rural Basins	Y	Y	Y	28
TR55	Urban Hydrology (NRCS)	Y	N	N	29
TR55 W SED (PROP)	Urban Hydrology with Sediment (Proposed)	Y	Y	Y	30
WASP5	Water Quality Analysis Simulation Progra	N	N	N	31
WEPP (WSHED)	Water Erosion Prediction Project Model (Watershed Version)	Y	Y	Y	32
WMM	Watershed Management Model	Y	N	N	33
WQRRS	Water Quality for River Reservoir Systems	N	N	N	34

MATRIX II - SECOND SCREENING LEVEL

TYPE OF EROSION/SEDIMENT PREDICTION

<i>ACRONYM</i>	<i>NAME</i>	<i>Deliv Ratio/ Sed Yld</i>	<i>Erosion Prevent Eval</i>	<i>Sediment Control Evaluation</i>	
				<i>Reservoir/ Pond</i>	<i>Small Controls</i>
AGNPS	Agricultural Non-Point Source Pollution Model	Y	Y	N	N
ANSWERS - 2000	Aerial Non-Point Source Watershed Environmental Response Simulation	Y	Y	N	N
Auto-QI	Automated Q-IILLUDAS	N	N	N	N
CREAMS/GLEAMS	Chemicals and Runoff in Agricultural Management Systems	Y	Y	N	N
DR3M-QUAL	Distributed Routing Rainfall Runoff Model-Quality	*	*	*	*
FESHM	Finite Element Sediment Hydrology Model	Y	Y	N	N
GWLF	Generalized Watershed Loading Functions	N	Y	N	N
HSPF	Hydrological Simulation Program-FORTRAN	Y	N	N	N
SEDCAD +, V3	Civil Software Version of SEDIMOT II	Y	Y	Y	N/Y
SEDIMOTII	Sedimentology by Distributed Modeling Techniques - Version II	Y	Y	Y	N/Y
SEDIMOTIII	Sedimentology by Distributed Modeling Techniques - Version III	Y	Y	Y	Y
SIMPLE (STORM)	Nonpoint Source Simulation Model	Y	Y	N	N
SIMPTM	Simplified Particle Transport Model	Y	?	N	N
SLAMM	Source Loading and Management Model	N	N	N	N
STORM	Storage, Treatment, Overflow, Runoff Model	N	N	Y	N
SWMM	Stormwater Management Model	N	N	N	N
SWRRBWQ	Simulation for Water Resources in Rural Basins	Y	Y	Y	N
TR55 W SED (PROP)	Urban Hydrology with Sediment (Proposed)	N	N	Y	Y
WEPP (WSHED)	Water Erosion Prediction Project Model (Watershed Version)	Y	Y	Y	Y

*Additional data being sought from USGS.

MATRIX III - FINAL MODEL CHARACTERISTICS

<i>MODEL CHARACTERISTICS NEEDED</i>	<i>SEDCAD+ V3</i>	<i>SEDIMOT II</i>	<i>SEDIMOT III</i>	<i>WEPP (WSHD)</i>
Type Simulation				
• Single storm	Y	Y	Y	?
• Multiple storm	Y	N	N	Y
Predict sediment discharge				
• Rill and interrill	Y	Y	Y	Y
• Concentrated flow	N	N	Y	Y
• Predict sediment size distribution	Y	Y	Y	Y
• Predict turbidity	N	N	N	N
Hydraulic computations				
• Variable time step to allow for small storage/large discharge	N	N	Y	Y
• Continuous functions for stage discharge & area	N	N	Y	Y
• Drop inlet	Y	Y	Y	Y
• Slotted risers	Y	N	Y	Y
• Slotted risers with rock fill wrapping	N	N	N	N
• Culverts outlets	Y**	N	Y	Y
• Open channel spillways - with control section	Y**	Y	Y	Y
• Open channel spillways - Without control section	Y**	Y	Y	Y
Evaluate impact of small controls				
• Rock fill checkdam	Y*	Y*	Y	Y
• Filter fence	N	N	Y	Y
• Straw bales	N	N	Y	Y
• Inlet filters	N	N	N	N
Evaluate impact of on site controls (erosion prevention)				
• Mulch (varying types)	Y	Y	Y	Y
• Vegetated cover	Y	Y	Y	Y
• Timing of establishment of vegetation	N	N	N	Y
• Geotextile blankets	Y	Y	Y	Y
• Channel bank stabilization	N	N	Y	Y
• Grade control structures	N	N	N	N
Account for instream flow above and below discharge point	N	N	N	N
History of use on urban watersheds	Y	Y	Y	N
Economic analysis capability	N	N	N	N

* Algorithms are not physically based or verified. At time of model development, they were the only ones available. More recent physically based models are available.

** The stability and accuracy of these procedures remain in question. Further information is needed.

Table 1. List of Search Keywords for Chattahoochee-Flint Literature Search.

Aquatic Macroinvertebrates	Pollution	stream
Sediment	NPS	regulations
Water quality	site	off-site controls
Turbidity	Sedimentation	Site characterization
Siltation	controls	Turbidity
Best Management Practice	small controls	instruments
Erosion	reservoirs	measurements
control	detention reservoirs	standards
controls	check dams	sediment concentration
prediction	filter fence	theory
models	porous structures	Water quality
mathematical models	vegetative filters	in-stream
modeling	yield	performance
prevention	trapping efficiency	standards
regulations	size	Urban
costs	size distribution	pollution
on-site control	Soil Erosion	runoff
Fish	Soil Loss	nonpoint source
Turbidity	Sediment	construction and
Reproduction impacts	control	pollution
Siltation	controls	modeling
Sediment	small controls	development and
Habitat degradation	reservoirs	pollution
Water quality	detention reservoirs	
Chattahoochee	check dams	
Piedmont	filter fence	
geography	porous structures	
physiography	vegetative filters	
soils	yield	
water quality	trapping efficiency	
hydrology	size	
sediment concentration	size distribution	
rivers	sediment graph	
watersheds	systems	
basins	models	
hydrologic soil groups	mathematical models	
curve numbers	transport	
runoff	deposition	
flooding	modeling	
	concentration	
	properties	
	prediction	